

according to Regulation (EC) No. 1907/2006 as amended by (EC) No. 1272/2008

Section 1. Identification of the Substance/Mixture and of the Company/Undertaking

- 1.1 Product Code:** C23
Product Name: Diesel Fuel Treatment
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant identified uses: Diesel fuel treatment
- 1.3 Details of the Supplier of the Safety Data Sheet:**
- | | | |
|--------------------------|---|---------------------------------------|
| Company Name: | CYCLO INDUSTRIES, INC.
902 SOUTH US HIGHWAY 1
JUPITER, FL 33477 USA | Phone Number:
(800)843-7813 |
| Web site address: | www.cyclo.com | |
| Email address: | ehs@cyclo.com | |
| Information: | First Aid Emergency (Outside U.S.) | (312)906-6194 |
- 1.4 Emergency telephone number:**
- | | | |
|---------------------------|-------------------------|---------------|
| Emergency Contact: | First Aid Emergency | (800)752-7869 |
| | CHEMTREC (703) 527-3887 | (800)424-9300 |

Section 2. Hazards Identification

- 2.1 Classification of the Substance or Mixture:**
Acute Toxicity: Inhalation, Category 4
Skin Corrosion/Irritation, Category 2
Carcinogenicity, Category 2
Aspiration Toxicity, Category 1
Serious Eye Damage/Eye Irritation, Category 2B
Aquatic Toxicity (Chronic), Category 2
Specific Target Organ Toxicity (repeated exposure), Category 2

- 2.2 Label Elements:**



GHS Signal Word: Danger

GHS Hazard Phrases:

H227: Combustible liquid.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation
H319: Causes serious eye damage.
H332: Harmful if inhaled.
H411: Toxic to aquatic life with long lasting effects.

GHS Precaution Phrases:

P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.
P233: Keep container tightly closed.
P260: Do not breathe dust/fume/gas/mist/vapours/spray.
P264: Wash hands thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.



SAFETY DATA SHEET

Diesel Fuel Treatment

P280: Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases:

P370+378: In case of fire use CO₂, dry chemical, foam or water spray to extinguish,

P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P363: Wash contaminated clothing before reuse.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

GHS Storage and Disposal Phrases:

P405: Store locked up.

P403+233: Store container tightly closed in well-ventilated place.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

2.3 Adverse Human Health No data available.

Effects and Symptoms:

Section 3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)/ REACH Registration No.	Concentration	EC No./ EC Index No.	GHS Classification
68476-30-2	Fuel oil, no. 2	92.0 -96.0 %	270-671-4 649-225-00-1	Carcinogen 2: H351
64742-95-6	SC-100 Solvent	0.892 -1.338 %	265-199-0 649-356-00-4	Asp. Toxic. 1: H304 Mutagen 1B: H340 Carcinogen 1B: H350
95-63-6	1,2,4-Trimethylbenzene	0.717 -0.94 %	202-436-9 601-043-00-3	Flam. Liq. 3: H226 Skin Corr. 2: H315 Eye Damage 2: H319 Acute Tox.(I) 4: H332 STOT (SE) 3: H335 H336 Aquatic (C) 2: H411
108-67-8	Mesitylene	0.1 -1.0 %	203-604-4 601-025-00-5	Flam. Liq. 3: H226 STOT (SE) 3: H335 H336 Aquatic (C) 2: H411
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	0.1 -1.0 %	265-198-5 649-424-00-3	Asp. Toxic. 1: H304
1330-20-7	Xylene (mixed isomers)	< 0.223 %	215-535-7 601-022-00-9	Flam. Liq. 3: H226 Acute Tox.(D) 4: H312 Skin Corr. 2: H315 Acute Tox.(I) 4: H332
25551-13-7	Benzene, Trimethyl-	< 0.223 %	247-099-9 NA	Flam. Liq. 3: H226 Skin Corr. 2: H315 Eye Damage 2B: H320 STOT (SE) 3: H335 H336 STOT (RE) 2: H373 Asp. Toxic. 1: H304 Aquatic (A) 2: H401 Aquatic (C) 2: H411
98-82-8	Cumene	< 0.09 %	202-704-5 601-024-00-X	Flam. Liq. 3: H226 Asp. Toxic. 1: H304 STOT (SE) 3: H335 H336



SAFETY DATA SHEET

Diesel Fuel Treatment

Revision: 09/06/2017
Supersedes Revision: 07/11/2017

100-41-4	Ethylbenzene	< 0.045 %	202-849-4	Aquatic (C) 2: H411 Flam. Liq. 2: H225
			601-023-00-4	Acute Tox.(I) 4: H332 STOT (RE) 2: H373 Asp. Toxic. 1: H304
91-20-3	Naphthalene	< 0.04 %	202-049-5	Acute Tox.(O) 4: H302
			601-052-00-2	Carcinogen 2: H351 Aquatic (A) 1: H400 Aquatic (C) 1: H410
108-05-4	Vinyl acetate	< 0.005 %	203-545-4	Flam. Liq. 2: H225
			607-023-00-0	Acute Tox.(I) 4: H332 Carcinogen 2: H351 STOT (SE) 3: H335

Section 4. First Aid Measures

- 4.1 Description of First Aid Measures:** If swallowed, do not induce vomiting and do not give liquids. If inhaled, remove to fresh air. If breathing is difficult, administer oxygen. If not breathing or if not heartbeat, give artificial respiration or CPR. In case of skin contact, wash with soap and large amounts of water. Remove contaminated clothing. If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call physician immediately if adverse reaction occurs.
- 4.2 Important Symptoms and Effects, Both Acute and Delayed:** Inhalation: Exposure to high vapor concentrations may produce headache, giddiness, vertigo and anesthetic stupor.

Section 5. Fire Fighting Measures

- 5.1 Suitable Extinguishing Media:** For small fires, Class B fire extinguishing media such as CO2, dry chemical, foam (AFFF/ATC) or water spray can be used.
- 5.2 Flammable Properties and Hazards:** This product has been determined to be a combustible liquid per the OSHA Hazard Communication Standard and should be handled accordingly. For additional fire related information, see NFPA 30 or the North American Emergency Response Guide 128.
No data available.
- Flash Pt:** 138.00 F (58.9 C) Method Used: Pensky-Marten Closed Cup
- Explosive Limits:** LEL: No data. UEL: No data.
- Autoignition Pt:** No data.
- 5.3 Fire Fighting Instructions:** Fire fighting should be attempted only by those who are adequately trained and equipped with proper protective equipment. Avoid using straight water streams. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible. Avoid excessive water spray application. Keep surrounding area cool with water spray from a distance and prevent further ignition of combustible material. Keep run-off water out of sewers and water sources.



Section 6. Accidental Release Measures

- 6.1 Protective Precautions, Protective Equipment and Emergency Procedures:** No data available.
- 6.2 Environmental Precautions:** No data available.
- 6.3 Methods and Material For Containment and Cleaning Up:** Keep public away. Isolate and evacuate area. Shut off source if safe to do so. Eliminate all ignition sources. Advise authorities and National Response Center (800)-424-8802 if substance has entered a watercourse or sewer. Notify local health and pollution control agencies, if appropriate. Contain liquid with sand or soil. Recover and return free product to proper containers. Use suitable absorbent materials such as vermiculite, sand or clay to clean up residual liquids.

Section 7. Handling and Storage

- 7.1 Precautions To Be Taken in Handling:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces - No smoking. Keep container tightly closed. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Keep out of the reach of children.
- 7.2 Precautions To Be Taken in Storing:** Store container tightly closed in well-ventilated place. Store locked up.

Section 8. Exposure Controls/Personal Protection

8.1 Exposure Parameters:

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
68476-30-2	Fuel oil, no. 2	ACGIH TLV	TLV: 100 mg/m3	
95-63-6	1,2,4-Trimethylbenzene	Europe	TWA: 100 mg/m3 (20 ppm)	
		France VL	TWA: 100 mg/m3 (20 ppm) STEL: 250 mg/m3 (50 ppm)	
108-67-8	Mesitylene	Europe	TWA: 100 mg/m3 (20 ppm)	
		France VL	TWA: 100 mg/m3 (20 ppm) STEL: 250 mg/m3 (50 ppm)	
1330-20-7	Xylene (mixed isomers)	ACGIH TLV	TLV: 100 ppm STEL: 150 ppm	
		Europe	TWA: 221 mg/m3 (50 ppm) STEL: 442 mg/m3 (100 ppm)	Skin Absorption
		France VL	TWA: 221 mg/m3 (50 ppm) STEL: 442 mg/m3 (100 ppm)	
		OSHA PELs Britain EH40	PEL: 100 ppm TWA: 220 mg/m3 (50 ppm) STEL: 441 mg/m3 (100 ppm)	
25551-13-7	Benzene, Trimethyl-	ACGIH TLV Britain EH40	TLV: 25 ppm TWA: 125 mg/m3 (25 ppm) STEL: ()	
98-82-8	Cumene	ACGIH TLV Europe	TLV: 50 ppm TWA: 100 mg/m3 (20 ppm) STEL: 250 mg/m3 (50 ppm)	Skin Absorption



SAFETY DATA SHEET

Diesel Fuel Treatment

Revision: 09/06/2017
Supersedes Revision: 07/11/2017

98-82-8 Cumene (continued)	France VL	TWA: 100 mg/m3 (20 ppm) STEL: 250 mg/m3 (50 ppm)	
	OSHA PELs Britain EH40	PEL: 50 ppm TWA: 125 mg/m3 (25 ppm) STEL: 250 mg/m3 (50 ppm)	Skin Absorption
100-41-4 Ethylbenzene	ACGIH TLV	TLV: 100 ppm STEL: 125 ppm	
	Europe	TWA: 442 mg/m3 (100 ppm) STEL: 884 mg/m3 (200 ppm)	Skin Absorption
	France VL	TWA: 88.4 mg/m3 (20 ppm) STEL: 442 mg/m3 (100 ppm)	
	OSHA PELs Britain EH40	PEL: 100 ppm TWA: 441 mg/m3 (100 ppm) STEL: 552 mg/m3 (125 ppm)	Skin Absorption
91-20-3 Naphthalene	ACGIH TLV	TLV: 10 ppm STEL: 15 ppm	
	Europe	TWA: 50 mg/m3 (10 ppm)	
	France VL	TWA: 50 mg/m3 (10 ppm)	
	OSHA PELs	PEL: 10 ppm	
108-05-4 Vinyl acetate	ACGIH TLV	TLV: 10 ppm STEL: 15 ppm	
	France VL	TWA: 30 mg/m3 (10 ppm)	

8.2 Exposure Controls:

8.2.1 Engineering Controls (Ventilation etc.): Local or general exhaust required when using at elevated temperatures that generate vapors or mists.

8.2.2 Personal protection equipment:

Eye Protection: No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields.

Protective Gloves: Neoprene, nitrile, polyvinyl (PVC), polyvinyl chloride and polyurethane gloves to prevent skin contact.

Other Protective Clothing: No data available.

Respiratory Equipment (Specify Type): Use approved organic vapor chemical cartridge or supplied air respirators when material produces vapors that exceed permissible limits or excessive vapors are generated. Observe respirator protection factor criteria cited in ANSI Z88.2.

Work/Hygienic/Maintenance Practices: No special protective clothing is normally required. Select protective clothing depending on industrial operations. Use mechanical ventilation equipment that is explosion-proof. No data available.



Section 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Physical States:	[] Gas [X] Liquid [] Solid
Appearance and Odor:	Clear red liquid with a slight petroleum odor.
pH:	No data.
Melting Point:	No data.
Boiling Point:	360.00 F (182.2 C) - 550.00 F (287.8 C)
Flash Pt:	138.00 F (58.9 C) Method Used: Pensky-Marten Closed Cup
Evaporation Rate:	No data.
Flammability (solid, gas):	No data available.
Explosive Limits:	LEL: No data. UEL: No data.
Vapor Pressure (vs. Air or mm Hg):	> 1 MM_HG at 100.0 F (37.8 C)
Vapor Density (vs. Air = 1):	4 - 5
Specific Gravity (Water = 1):	No data.
Density:	6.97 - 7.17
Solubility in Water:	No data.
Octanol/Water Partition Coefficient:	No data.
Autoignition Pt:	No data.
Decomposition Temperature:	No data.
Viscosity:	No data.

9.2 Other Information

Percent Volatile: 10.0 % by weight.

Section 10. Stability and Reactivity

10.1 Reactivity:	No data available.
10.2 Stability:	Unstable [] Stable [X]
10.3 Conditions To Avoid - Hazardous Reactions:	No data available.
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
10.4 Conditions To Avoid - Instability:	Excessive heat, sources of ignition and open flames.
10.5 Incompatibility - Materials To Avoid:	Strong oxidizers such as nitrates, perchlorates, chlorine flourine.
10.6 Hazardous Decomposition or Byproducts:	Combustion produces carbon monoxide, aldehydes, aromatic and other hydrocarbons.



Section 11. Toxicological Information

11.1 Information on Toxicological Effects:

Lifetime skin painting studies in animals with similar distillate fuels have produced weak to moderate carcinogenic activity following prolonged and repeated exposure. Similar middle distillates, when tested at nonirritating dose levels, did not show any significant carcinogenic activity indicating that this tumorigenic response is likely related to chronic irritation and not to dose. Repeated dermal application has produced severe irritation and systemic toxicity in subacute toxicity studies. Some components of this product, have been shown to produce a species specific, sex hormonal dependent kidney lesion in male rats from repeated oral or inhalation exposure. Subsequent research has shown that the kidney damage develops via the formation of a alpha-2u-globulin, a mechanism unique to the male rat. Humans do not form alpha-2u-globulin, therefore, the kidney effects resulting from this mechanism are not relevant in humans. Some components of this product were found to be positive in a few mutagenicity tests while negative in the majority of others. The exact relationship between these results and human health is not known.

Summary of health effect data on distillate fuel components:

This products sub-components may contain >.01% naphthalene. Exposure to naphthalene at 30 pm for two years caused lung tumors in female mice. Male mice with the same exposure did not develop tumors. Exposure to 10-60 ppm naphthalene for 2 years caused tumors in the tissue lining of the nose and respiratory tract in male and female rats. Oral administration of 133-267 mg/kg/day of naphthalene in mice for up to 90 days did not produce mortality, systemic toxicity, adversely affect organ or body weight or produce changes in blood. Repeated oral administration of naphthalene produced an anemia in dogs. Repeated intraperitoneal doses of naphthalene produced lung damage in mice. Repeated high doses of naphthalene has caused the formation of cataracts and retinotoxicity in the eyes of rats and rabbits due to accumulation of 1,2-naphthoquinone, a toxic metabolite. Effects in human eyes is uncertain and not well documented. Pregnant rats administered intraperitoneal doses of naphthalene during gestation gave birth to offspring that had delayed heart and bone development. Pregnant mice given near lethal doses of naphthalene showed no significant maternal toxicity and a reduction in the number of pups per litter, but no gross abnormalities in offspring. Suppressed spermiogenesis and progeny development have been reported in mice, rats and guinea pigs after exposure to high concentrations of naphthalene in their drinking water. Certain groups or individuals, i.e., infants, Semites, Arabs, Asians and Blacks, with a certain blood enzyme deficiency (glucose-6-phosphate dehydrogenase) are particularly susceptible to hemolytic agents and can rapidly develop hemolytic anemia and systemic poisoning from ingestion or inhalation of naphthalene.

CAS# 68476-30-2:

Other Studies:, TDLo, Skin, Species: Rabbit, 100.0 ML/KG, 12 D.

Results:

Skin and Appendages: Skin: After systemic exposure: Dermatitis, irritative.

Nutritional and Gross Metabolic:Weight loss or decreased weight gain.

Related to Chronic Data - death.

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982," MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983 Volume, Vol/p/yr: 1,1, 1983

Acute toxicity, LD50, Oral, Rat, 12.00 GM/KG.



SAFETY DATA SHEET

Diesel Fuel Treatment

Revision: 09/06/2017
Supersedes Revision: 07/11/2017

Results:

Behavioral: Somnolence (general depressed activity).

- Advances in Modern Environmental Toxicology., Senate Press, Inc., P.O. Box 252, Princeton Junction, NJ 08550, Vol/p/yr: 6,1, 1984

Acute toxicity, LD (Lethal dose), Skin, Species: Rabbit, > 5.000 GM/KG.

Results:

Behavioral: Tremor.

Behavioral: Convulsions or effect on seizure threshold.

- Advances in Modern Environmental Toxicology., Senate Press, Inc., P.O. Box 252, Princeton Junction, NJ 08550, Vol/p/yr: 6,1, 1984

Tumorigenic Effects:, TDLo, Skin, Mouse, 243.0 GM/KG, 97 W.

Results:

Tumorigenic: Carcinogenic by RTECS criteria.

Skin and Appendages: Other: Tumors.

- Fundamental and Applied Toxicology., Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 9,297, 1987

Standard Draize Test, Skin, Species: Rabbit, 500.0 MG, 24 H, Moderate.

Results:

Brain and Coverings: Changes in surface EEG.

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982," MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983 Volume, Vol/p/yr: 1,1, 1983

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, 30 S, Mild.

Results:

Behavioral: Somnolence (general depressed activity).

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982," MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983 Volume, Vol/p/yr: 1,1, 1983

Chronic Toxicological Effects:

Summary of health effect information on diesel engine exhaust:

Chronic inhalation studies of whole diesel engine exhaust in mice and rats produced a significant increase in lung tumors. Combustion of kerosene and/or diesel fuels produces gases and particulates which include carbon monoxide, carbon dioxide, oxides of nitrogen and/or sulfur and hydrocarbons. Significant exposure to carbon monoxide vapors decreases the oxygen carrying capacity of the blood and may cause tissue hypoxia via formation of carboxyhemoglobin.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
68476-30-2	Fuel oil, no. 2	n.a.	2B	A3	n.a.
64742-95-6	SC-100 Solvent	n.a.	n.a.	n.a.	n.a.
95-63-6	1,2,4-Trimethylbenzene	n.a.	n.a.	n.a.	n.a.
108-67-8	Mesitylene	n.a.	n.a.	n.a.	n.a.
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	n.a.	n.a.	n.a.	n.a.
1330-20-7	Xylene (mixed isomers)	n.a.	3	A4	n.a.



SAFETY DATA SHEET

Diesel Fuel Treatment

Revision: 09/06/2017
Supersedes Revision: 07/11/2017

25551-13-7	Benzene, Trimethyl-	n.a.	n.a.	n.a.	n.a.
98-82-8	Cumene	Possible	2B	n.a.	n.a.
100-41-4	Ethylbenzene	n.a.	2B	A3	n.a.
91-20-3	Naphthalene	Possible	2B	A4	n.a.
108-05-4	Vinyl acetate	n.a.	2B	A3	n.a.

Section 12. Ecological Information

- 12.1 Toxicity:** Product can cause fouling of shoreline and may be harmful to aquatic life in low concentrations. The 96 hour LL50 values for an accommodated fraction (WAF) of fuel oil ranged from 3.2 to 65 mg/l in fish and 2-210 mg/l in invertebrates. EL 50 values for inhibition of algal growth ranged from 1.8 to 2.9 mg/l for No. 2 fuel oil and from 10 to 78 mg/l for diesel fuel. This product does not concentrate or accumulate in the food chain. If released to soil and water, this product is expected to biodegrade under both aerobic and anaerobic conditions.
- Environmental Hazards: TOXIC TO AQUATIC ORGANISMS. MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT IF EXPOSED IN LARGE AMOUNTS.
- Environmental Note: THIS PRODUCT CONTAINS COMPONENTS WHICH MAY BE PERSISTENT IN THE ENVIRONMENT.
- 12.2 Persistence and Degradability:** No data available.
- 12.3 Bioaccumulative Potential:** No data available.
- 12.4 Mobility in Soil:** No data available.
- 12.5 Results of PBT and vPvB assessment:** No data available.
- 12.6 Other adverse effects:** No data available.

Section 13. Disposal Considerations

- 13.1 Waste Disposal Method:** Dispose of contents/container in accordance with local/regional/national/international regulation.

Section 14. Transport Information

14.1 LAND TRANSPORT (European ADR/RID):

ADR/RID Shipping Name: Flammable Liquid, n.o.s (Fuel Oil No. 2, SC-100 Solvent), Ltd Qty
UN Number: 1993 **Packing Group:** III
Hazard Class: 3 - FLAMMABLE LIQUID **ADR Classification:** 3

14.2 MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Flammable Liquid, n.o.s (Fuel Oil No. 2, SC-100 Solvent), Ltd Qty
UN Number: 1993 **Packing Group:** III
Hazard Class: 3 - FLAMMABLE LIQUID
IMDG MFAG Number:
IMDG EMS Page: **Marine Pollutant:** No



SAFETY DATA SHEET

Diesel Fuel Treatment

14.3 AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Flammable Liquid, n.o.s (Fuel Oil No. 2, SC-100 Solvent), Ltd Qty
UN Number: 1993 **Packing Group:** III
Hazard Class: 3 - FLAMMABLE LIQUID **IATA Classification:** 3

Section 15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
68476-30-2	Fuel oil, no. 2	No	No	No
64742-95-6	SC-100 Solvent	No	No	No
95-63-6	1,2,4-Trimethylbenzene	No	No	Yes
108-67-8	Mesitylene	No	No	No
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	No	No	No
1330-20-7	Xylene (mixed isomers)	No	Yes 100 LB	Yes
25551-13-7	Benzene, Trimethyl-	No	No	No
98-82-8	Cumene	No	Yes 5000 LB	Yes
100-41-4	Ethylbenzene	No	Yes 1000 LB	Yes
91-20-3	Naphthalene	No	Yes 100 LB	Yes
108-05-4	Vinyl acetate	Yes 1000 LB	Yes 5000 LB	Yes

CAS # Hazardous Components (Chemical Name)

Other US EPA or State Lists

68476-30-2	Fuel oil, no. 2	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
64742-95-6	SC-100 Solvent	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
95-63-6	1,2,4-Trimethylbenzene	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 2716; NY Part 597: No; PA HSL: Yes - E; SC TAP: No; WI Air: No
108-67-8	Mesitylene	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
1330-20-7	Xylene (mixed isomers)	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: CMR, Part 5; NC TAP: Yes; NJ EHS: Yes - 2014; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes
25551-13-7	Benzene, Trimethyl-	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -



SAFETY DATA SHEET

Diesel Fuel Treatment

Revision: 09/06/2017

Supersedes Revision: 07/11/2017

Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: Yes

98-82-8 Cumene

CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: Yes: Canc.; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 0542; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes

100-41-4 Ethylbenzene

CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: Yes: Canc.; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 0851; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes

91-20-3 Naphthalene

CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A PAIR; CA PROP.65: Yes: Canc.; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 1322; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes

108-05-4 Vinyl acetate

CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 1998; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes

CAS # Hazardous Components (Chemical Name)**International Regulatory Lists**

68476-30-2 Fuel oil, no. 2

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

64742-95-6 SC-100 Solvent

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

95-63-6 1,2,4-Trimethylbenzene

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

108-67-8 Mesitylene

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

64742-94-5 Solvent naphtha (petroleum), Heavy arom.

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

1330-20-7 Xylene (mixed isomers)

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

25551-13-7 Benzene, Trimethyl-

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

98-82-8 Cumene

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: 081-01 (4)

100-41-4 Ethylbenzene

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: 116-01 (4)

91-20-3 Naphthalene

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes


108-05-4 Vinyl acetate

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: 146-01 (4)

Section 16. Other Information

Revision Date: 09/06/2017

Hazard Rating System:



Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting from use of or reliance upon this information.