

according to Regulation (EC) No. 1907/2006 as amended by (EC) No. 1272/2008

Section 1. Identification of the Substance/Mixture and of the Company/Undertaking

- 1.1 Product Code:** C260, C261
Product Name: 6XT Diesel Fuel Treatment
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant identified uses: Diesel fuel treatment
- 1.3 Details of the Supplier of the Safety Data Sheet:**
- | | | |
|--------------------------|---|---------------------------------------|
| Company Name: | CYCLO INDUSTRIES, INC.
902 SOUTH US HIGHWAY 1
JUPITER, FL 33477 USA | Phone Number:
(800)843-7813 |
| Web site address: | www.cyclo.com | |
| Email address: | ehs@cyclo.com | |
| Information: | First Aid Emergency (Outside U.S.) | (312)906-6194 |
- 1.4 Emergency telephone number:**
- | | | |
|---------------------------|-------------------------|---------------|
| Emergency Contact: | First Aid Emergency | (800)752-7869 |
| | CHEMTREC (703) 527-3887 | (800)424-9300 |

Section 2. Hazards Identification

- 2.1 Classification of the Substance or Mixture:**
Skin Corrosion/Irritation, Category 2
Carcinogenicity, Category 2
Aquatic Toxicity (Chronic), Category 2
Acute Toxicity: Inhalation, Category 4
Serious Eye Damage/Eye Irritation, Category 2B
Germ Cell Mutagenicity, Category 1B
Aspiration Toxicity, Category 1
Specific Target Organ Toxicity (repeated exposure), Category 2

- 2.2 Label Elements:**



GHS Signal Word: **Danger**

GHS Hazard Phrases:

H227: Combustible liquid.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H351: Suspected of causing cancer
H373: May cause damage to organs through prolonged or repeated exposure.
H411: Toxic to aquatic life with long lasting effects.



SAFETY DATA SHEET

6XT Diesel Fuel Treatment

GHS Precaution Phrases:

- P201: Obtain special instructions before use.
 P202: Do not handle until all safety precautions have been read and understood.
 P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.
 P233: Keep container tightly closed.
 P260: Do not breathe dust/fume/gas/mist/vapors/spray.
 P264: Wash hands thoroughly after handling.
 P273: Avoid release to the environment.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases:

- P370+378: In case of fire, use foam, alcohol foam, carbon dioxide, dry chemical or water fog for extinction.
 P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P331: Do NOT induce vomiting.
 P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
 P332+313: If skin irritation occurs, get medical advice/attention.
 P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+313: If eye irritation persists, get medical advice/attention.
 P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

GHS Storage and Disposal Phrases:

- P403+235: Store in cool/well-ventilated place.
 P405: Store locked up.
 P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

2.3 Adverse Human Health No data available.**Effects and Symptoms:**

Medical Conditions Pre-existing skin conditions and respiratory disorders may be aggravated by exposures to
Generally Aggravated components of this product.

By Exposure:
Section 3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)/ REACH Registration No.	Concentration	EC No./ EC Index No.	GHS Classification
68476-30-2	Fuel oil, no. 2	90.0 -95.0 %	270-671-4 649-225-00-1	Carcinogen 2: H351
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	1.3 -3.0 %	265-198-5 649-424-00-3	Asp. Toxic. 1: H304
111-76-2	Ethanol, 2-Butoxy-	2.0 %	203-905-0 603-014-00-0	Acute Tox.(O) 4: H302 Acute Tox.(D) 4: H312 Skin Corr. 2: H315 Eye Damage 2A: H319 Acute Tox.(I) 4: H332
64742-95-6	SC-100 Solvent	1.0 -2.0 %	265-199-0 649-356-00-4	Asp. Toxic. 1: H304 Mutagen 1B: H340 Carcinogen 1B: H350
95-63-6	1,2,4-Trimethylbenzene	0.2 -1.0 %	202-436-9 601-043-00-3	Flam. Liq. 3: H226 Skin Corr. 2: H315 Eye Damage 2: H319 Acute Tox.(I) 4: H332



SAFETY DATA SHEET

6XT Diesel Fuel Treatment

Revision: 09/06/2017

Supersedes Revision: 02/12/2015

Product ID	Chemical Name	Concentration	Product Code	Hazard Statements
91-20-3	Naphthalene	0.21 -0.99 %	202-049-5 601-052-00-2	STOT (SE) 3: H335 H336 Aquatic (C) 2: H411 Acute Tox.(O) 4: H302 Carcinogen 2: H351 Aquatic (A) 1: H400 Aquatic (C) 1: H410
104-76-7	1-Hexanol, 2-Ethyl-	0.07 -0.33 %	203-234-3 NA	Skin Corr. 2: H315 Eye Damage 2: H319 Acute Tox.(I) 4: H332 STOT (SE) 3: H335
1330-20-7	Xylene (mixed isomers)	< 0.066 %	215-535-7 601-022-00-9	Flam. Liq. 3: H226 Acute Tox.(D) 4: H312 Skin Corr. 2: H315 Acute Tox.(I) 4: H332
98-82-8	Cumene	< 0.033 %	202-704-5 601-024-00-X	Flam. Liq. 3: H226 Asp. Toxic. 1: H304 STOT (SE) 3: H335 H336 Aquatic (C) 2: H411
108-67-8	Mesitylene	< 0.026 %	203-604-4 601-025-00-5	Flam. Liq. 3: H226 STOT (SE) 3: H335 H336 Aquatic (C) 2: H411

Section 4. First Aid Measures

- 4.1 Description of First Aid Measures:** If swallowed, do not induce vomiting. Rinse mouth. If inhaled, remove to fresh air. If not breathing, give artificial respiration. In case of skin contact, wash with soap and large amounts of water. Remove contaminated clothing. If in eyes, flush eyes with large amounts of tepid water for at least 15 minutes. Call physician immediately if adverse reaction occurs.
- 4.2 Important Symptoms and Effects, Both Acute and Delayed:** Exposure to high concentrations may produce headache, giddiness, vertigo and aesthetic stupor.

Section 5. Fire Fighting Measures

- 5.1 Suitable Extinguishing Media:** For small fires, Class B fire extinguishing media such as CO₂, dry chemical, foam (AFFF/ATC) or water spray can be used. For large fires, water spray, fog or foam (AFFF/ATC) can be used. Fire fighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.
- 5.2 Flammable Properties and Hazards:** This product has been determined to be a combustible liquid per the OSHA Hazard Communication Standard and should be handled accordingly. For additional fire related information, see NFPA 30 or the North American Emergency Response Guide 128.
No data available.
- Flash Pt:** 60.60 C (141.1 F) Method Used: Pensky-Marten Closed Cup
- Explosive Limits:** LEL: No data. UEL: No data.
- Autoignition Pt:** No data.
- 5.3 Fire Fighting Instructions:** Use NIOSH/MSHA approved positive pressure self-contained breathing apparatus and protective equipment. Avoid using straight water streams. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and spray from as far a distance as possible. Avoid excessive water spray application. Keep surrounding area cool with water spray from a distance and prevent further ignition of combustible material. Keep run-off out of sewers and water sources.



Section 6. Accidental Release Measures

- 6.1 Protective Precautions, Protective Equipment and Emergency Procedures:** No data available.
- 6.2 Environmental Precautions:** No data available.
- 6.3 Methods and Material For Containment and Cleaning Up:** Keep public away. Isolate and evacuate area. Shut off source if safe to do so. Eliminate all ignition sources. Advise authorities and National Response Center if substance has entered a watercourse or sewer. Notify local health and pollution control agencies, if appropriate. Contain liquid with sand or soil. Recover and return free product to proper containers. Use suitable absorbent materials such as vermiculite, sand, or clay to clean up residual liquids.

Section 7. Handling and Storage

- 7.1 Precautions To Be Taken in Handling:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces - No smoking. Keep container tightly closed. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Keep out of the reach of children.
- 7.2 Precautions To Be Taken in Storing:** Store locked up. Store in cool/well-ventilated place.

Section 8. Exposure Controls/Personal Protection

8.1 Exposure Parameters:

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
68476-30-2	Fuel oil, no. 2	ACGIH TLV	TLV: 100 mg/m3	
111-76-2	Ethanol, 2-Butoxy-	ACGIH TLV	TLV: 20 ppm	
		Europe	TWA: 98 mg/m3 (20 ppm) STEL: 246 mg/m3 (50 ppm)	Skin Absorption
		France VL	TWA: 9.8 mg/m3 (2 ppm) STEL: 147.6 mg/m3 (30 ppm)	
		OSHA PELs	PEL: 50 ppm	
		Britain EH40	TWA: 123 mg/m3 (25 ppm) STEL: 246 mg/m3 (50 ppm)	Skin Absorption
95-63-6	1,2,4-Trimethylbenzene	Europe	TWA: 100 mg/m3 (20 ppm)	
		France VL	TWA: 100 mg/m3 (20 ppm) STEL: 250 mg/m3 (50 ppm)	
91-20-3	Naphthalene	ACGIH TLV	TLV: 10 ppm STEL: 15 ppm	
		Europe	TWA: 50 mg/m3 (10 ppm)	
		France VL	TWA: 50 mg/m3 (10 ppm)	
		OSHA PELs	PEL: 10 ppm	
1330-20-7	Xylene (mixed isomers)	ACGIH TLV	TLV: 100 ppm STEL: 150 ppm	
		Europe	TWA: 221 mg/m3 (50 ppm) STEL: 442 mg/m3 (100 ppm)	Skin Absorption
		France VL	TWA: 221 mg/m3 (50 ppm) STEL: 442 mg/m3 (100 ppm)	



SAFETY DATA SHEET

6XT Diesel Fuel Treatment

Revision: 09/06/2017
Supersedes Revision: 02/12/2015

1330-20-7 Xylene (mixed isomers) (continued)	OSHA PELs	PEL: 100 ppm	
	Britain EH40	TWA: 220 mg/m3 (50 ppm) STEL: 441 mg/m3 (100 ppm)	
98-82-8 Cumene	ACGIH TLV	TLV: 50 ppm	
	Europe	TWA: 100 mg/m3 (20 ppm) STEL: 250 mg/m3 (50 ppm)	Skin Absorption
	France VL	TWA: 100 mg/m3 (20 ppm) STEL: 250 mg/m3 (50 ppm)	
	OSHA PELs	PEL: 50 ppm	
108-67-8 Mesitylene	Britain EH40	TWA: 125 mg/m3 (25 ppm) STEL: 250 mg/m3 (50 ppm)	Skin Absorption
	Europe	TWA: 100 mg/m3 (20 ppm)	
	France VL	TWA: 100 mg/m3 (20 ppm) STEL: 250 mg/m3 (50 ppm)	

8.2 Exposure Controls:

8.2.1 Engineering Controls (Ventilation etc.): Local or general exhaust required when using at elevated temperatures that generate vapors or mists.

8.2.2 Personal protection equipment:

- Eye Protection:** No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields.
- Protective Gloves:** Neoprene, nitrile, PVA, polyvinyl chloride and polyurethane gloves to prevent skin contact.
- Other Protective Clothing:** No data available.
- Respiratory Equipment (Specify Type):** Use approved organic vapor chemical cartridge or supplied air respirators when material produces vapors that exceed permissible limits or excessive vapors are generated. Observe respirator protection factor criteria cited in ANSI Z88.2. Self-contained breathing apparatus should be used for fire fighting.
- Work/Hygienic/Maintenance Practices:** No special clothing is normally required. Select protective clothing depending on industrial operations. Use mechanical ventilation equipment that is explosion-proof.
No data available.

Section 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

- Physical States:** [] Gas [X] Liquid [] Solid
- Appearance and Odor:** Transparent, reddish brown liquid with petroleum odor.
- pH:** No data.
- Melting Point:** No data.
- Boiling Point:** 360.00 F (182.2 C) - 550.00 F (287.8 C)
- Flash Pt:** 60.60 C (141.1 F) Method Used: Pensky-Marten Closed Cup
- Evaporation Rate:** No data.
- Flammability (solid, gas):** No data available.
- Explosive Limits:** LEL: No data. UEL: No data.
- Vapor Pressure (vs. Air or mm Hg):** No data.
- Vapor Density (vs. Air = 1):** No data.



SAFETY DATA SHEET

6XT Diesel Fuel Treatment

Specific Gravity (Water = 1):	0.836 - 0.856
Density:	6.972 - 7.139 at 70.0 F (21.1 C)
Solubility in Water:	No data.
Octanol/Water Partition	No data.
Coefficient:	
Autoignition Pt:	No data.
Decomposition Temperature:	No data.
Viscosity:	water thin

9.2 Other Information

Percent Volatile: 10.0 % by weight.

Section 10. Stability and Reactivity

- 10.1 Reactivity:** No data available.
- 10.2 Stability:** Unstable [] Stable [X]
- 10.3 Conditions To Avoid - Hazardous Reactions:** No data available.
- Possibility of Hazardous Reactions:** Will occur [] Will not occur [X]
- 10.4 Conditions To Avoid - Instability:** This material is stable at 70F, 760 mm pressure.
- 10.5 Incompatibility - Materials To Avoid:** Strong oxidizers such as nitrates, perchlorates, chlorine, flourine.
- 10.6 Hazardous Decomposition or Byproducts:** Combustion produces carbon monoxide, aldehydes, aromatic and other hydrocarbons.

Section 11. Toxicological Information

- 11.1 Information on Toxicological Effects:** Lifetime skin painting studies in animals with similar distillate fuels have produced weak to moderate carcinogenic activity following prolonged and repeated exposure. Similar middle distillates, when tested at nonirritating dose levels, did not show any significant carcinogenic activity indicating that this tumorigenic response is likely related to chronic irritation and not to dose. Repeated dermal application has produced severe irritation and systemic toxicity in subacute toxicity studies. Some components of this product, have been shown to produce a species specific, sex hormonal dependent kidney lesion in male rats from repeated oral or inhalation exposure. Subsequent research has shown that the kidney damage develops via the formation of a alpha-2u-globulin, a mechanism unique to the male rat. Humans do not form alpha-2u-globulin, therefore, the kidney effects resulting from this mechanism are not relevant in humans. Some components of this product were found to be positive in a few mutagenicity tests while negative in the majority of others. The exact relationship between these results and human health is not known.

Summary of health effect data on distillate fuel components:

This products sub-components may contain >.01% naphthalene. Exposure to naphthalene at 30 pm for two years caused lung tumors in female mice. Male mice with the same exposure did not develop tumors. Exposure to 10-60 ppm naphthalene for 2 years caused tumors in the tissue lining of the nose and respiratory tract in male and female rats. Oral administration of 133-267 mg/kg/day of naphthalene in mice for up to 90



SAFETY DATA SHEET

6XT Diesel Fuel Treatment

Revision: 09/06/2017

Supersedes Revision: 02/12/2015

days did not produce mortality, systemic toxicity, adversely affect organ or body weight or produce changes in blood. Repeated oral administration of naphthalene produced an anemia in dogs. Repeated intraperitoneal doses of naphthalene produced lung damage in mice. Repeated high doses of naphthalene has caused the formation of cataracts and retinotoxicity in the eyes of rats and rabbits due to accumulation of 1,2-naphthoquinone, a toxic metabolite. Effects in human eyes is uncertain and not well documented. Pregnant rats administered intraperitoneal doses of naphthalene during gestation gave birth to offspring that had delayed heart and bone development. Pregnant mice given near lethal doses of naphthalene showed no significant maternal toxicity and a reduction in the number of pups per litter, but no gross abnormalities in offspring. Suppressed spermiogenesis and progeny development have been reported in mice, rats and guinea pigs after exposure to high concentrations of naphthalene in their drinking water. Certain groups or individuals, i.e., infants, Semites, Arabs, Asians and Blacks, with a certain blood enzyme deficiency (glucose-6-phosphate dehydrogenase) are particularly susceptible to hemolytic agents and can rapidly develop hemolytic anemia and systemic poisoning from ingestion or inhalation of naphthalene.

CAS# 68476-30-2:

Other Studies:, TDLo, Skin, Species: Rabbit, 100.0 ML/KG, 12 D.

Results:

Skin and Appendages: Skin: After systemic exposure: Dermatitis, irritative.

Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

Related to Chronic Data - death.

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982," MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983
Volume, Vol/p/yr: 1,1, 1983

Acute toxicity, LD50, Oral, Rat, 12.00 GM/KG.

Results:

Behavioral: Somnolence (general depressed activity).

- Advances in Modern Environmental Toxicology., Senate Press, Inc., P.O. Box 252, Princeton Junction, NJ 08550, Vol/p/yr: 6,1, 1984

Acute toxicity, LD (Lethal dose), Skin, Species: Rabbit, > 5.000 GM/KG.

Results:

Behavioral: Tremor.

Behavioral: Convulsions or effect on seizure threshold.

- Advances in Modern Environmental Toxicology., Senate Press, Inc., P.O. Box 252, Princeton Junction, NJ 08550, Vol/p/yr: 6,1, 1984

Tumorigenic Effects:, TDLo, Skin, Mouse, 243.0 GM/KG, 97 W.

Results:

Tumorigenic: Carcinogenic by RTECS criteria.

Skin and Appendages: Other: Tumors.

- Fundamental and Applied Toxicology., Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 9,297, 1987

Standard Draize Test, Skin, Species: Rabbit, 500.0 MG, 24 H, Moderate.

Results:

Brain and Coverings: Changes in surface EEG.

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982,"



SAFETY DATA SHEET

6XT Diesel Fuel Treatment

Revision: 09/06/2017
Supersedes Revision: 02/12/2015

MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983
Volume, Vol/p/yr: 1,1, 1983

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, 30 S, Mild.

Results:

Behavioral: Somnolence (general depressed activity).

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982,"

MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983

Volume, Vol/p/yr: 1,1, 1983

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
68476-30-2	Fuel oil, no. 2	n.a.	2B	A3	n.a.
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	n.a.	n.a.	n.a.	n.a.
111-76-2	Ethanol, 2-Butoxy-	n.a.	3	A3	n.a.
64742-95-6	SC-100 Solvent	n.a.	n.a.	n.a.	n.a.
95-63-6	1,2,4-Trimethylbenzene	n.a.	n.a.	n.a.	n.a.
91-20-3	Naphthalene	Possible	2B	A4	n.a.
104-76-7	1-Hexanol, 2-Ethyl-	n.a.	n.a.	n.a.	n.a.
1330-20-7	Xylene (mixed isomers)	n.a.	3	A4	n.a.
98-82-8	Cumene	Possible	2B	n.a.	n.a.
108-67-8	Mesitylene	n.a.	n.a.	n.a.	n.a.

Section 12. Ecological Information

- 12.1 Toxicity:** Product can cause fouling of shoreline and may be harmful to aquatic life in low concentrations. The 96 hour LL50 values for an accomadated fraction (WAF) of fuel oil ranged from 3.2 to 65 mg/l in fish and 2-210 mg/l in invertebrates. EL 50 values for inhibition of algal growth ranged from 1.8 to 2.9 mg/l for No. 2 fuel oil and from 10 to 78 mg/l for diesel fuel. This product does not concentrate or accumulate in the food chain. If released to soil and water, this product is expected to biodegrade under both aerobic and anaerobic conditions.
- Environmental Hazards: TOXIC TO AQUATIC ORGANISMS. MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
- Environmental Fate: THIS PRODUCT CONTAINS COMPONENTS WHICH MAY BE PERSISTENT IN THE ENVIRONMENT.
- 12.2 Persistence and Degradability:** No data available.
- 12.3 Bioaccumulative Potential:** No data available.
- 12.4 Mobility in Soil:** No data available.
- 12.5 Results of PBT and vPvB assessment:** No data available.
- 12.6 Other adverse effects:** No data available.



Section 13. Disposal Considerations

13.1 Waste Disposal Method: Dispose of contents/container in accordance with local/regional/national/international regulation.

Section 14. Transport Information

14.1 LAND TRANSPORT (European ADR/RID):

ADR/RID Shipping Name: Not-Regulated
UN Number:
Hazard Class:

14.2 MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Not-Regulated
UN Number:
Hazard Class:

Packing Group:

IMDG MFAG Number:

IMDG EMS Page:

Marine Pollutant: No

14.3 AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Not-Regulated

Section 15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
68476-30-2	Fuel oil, no. 2	No	No	No
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	No	No	No
111-76-2	Ethanol, 2-Butoxy-	No	No	Yes-Cat. N230
64742-95-6	SC-100 Solvent	No	No	No
95-63-6	1,2,4-Trimethylbenzene	No	No	Yes
91-20-3	Naphthalene	No	Yes 100 LB	Yes
104-76-7	1-Hexanol, 2-Ethyl-	No	No	No
1330-20-7	Xylene (mixed isomers)	No	Yes 100 LB	Yes
98-82-8	Cumene	No	Yes 5000 LB	Yes
108-67-8	Mesitylene	No	No	No

CAS # Hazardous Components (Chemical Name)

Other US EPA or State Lists

68476-30-2	Fuel oil, no. 2	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
111-76-2	Ethanol, 2-Butoxy-	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Yes - Cat.; NC TAP: Yes - Cat.; NJ EHS: Yes - Cat.; NY Part 597: No; PA HSL: Yes - 1; SC TAP: Yes - Cat.; WI Air: Yes
64742-95-6	SC-100 Solvent	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -



SAFETY DATA SHEET

6XT Diesel Fuel Treatment

Revision: 09/06/2017

Supersedes Revision: 02/12/2015

Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

95-63-6 1,2,4-Trimethylbenzene

CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 2716; NY Part 597: No; PA HSL: Yes - E; SC TAP: No; WI Air: No

91-20-3 Naphthalene

CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A PAIR; CA PROP.65: Yes: Canc.; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 1322; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes

104-76-7 1-Hexanol, 2-Ethyl-

CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 8D TERM; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No

1330-20-7 Xylene (mixed isomers)

CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: CMR, Part 5; NC TAP: Yes; NJ EHS: Yes - 2014; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes

98-82-8 Cumene

CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: Yes: Canc.; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 0542; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes

108-67-8 Mesitylene

CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

CAS # Hazardous Components (Chemical Name)

International Regulatory Lists

68476-30-2 Fuel oil, no. 2

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

64742-94-5 Solvent naphtha (petroleum), Heavy arom.

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

111-76-2 Ethanol, 2-Butoxy-

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

64742-95-6 SC-100 Solvent

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

95-63-6 1,2,4-Trimethylbenzene

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

91-20-3 Naphthalene

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

104-76-7 1-Hexanol, 2-Ethyl-

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

1330-20-7 Xylene (mixed isomers)

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

98-82-8 Cumene

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: 081-01 (4)

108-67-8 Mesitylene

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes




SAFETY DATA SHEET

6XT Diesel Fuel Treatment

Section 16. Other Information

Revision Date: 09/06/2017

Hazard Rating System:



Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting from use of or reliance upon this information.