

1. Product and Company Identification

Product Code: C33V
Product Name: Silicone Spray
Company Name: CYCLO INDUSTRIES, INC.
902 SOUTH US HIGHWAY 1
JUPITER, FL 33477
Phone Number: (800)843-7813

Web site address: www.cyclo.com
Email address: ehs@cyclo.com

Emergency Contact: First Aid Emergency (800)752-7869
CHEMTREC (703) 527-3887 (800)424-9300

Information: First Aid Emergency (Outside U.S.) (312)906-6194

Intended Use: Silicone

2. Hazards Identification

Flammable Aerosols, Category 1
Skin Corrosion/Irritation, Category 2
Specific Target Organ Toxicity (single exposure), Category 3
Aspiration Toxicity, Category 1



GHS Signal Word: **Danger**

GHS Hazard Phrases: H222: Extremely flammable aerosol.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H336: May cause drowsiness or dizziness
H410: Toxic to aquatic life with long lasting effects
H229: Pressurized container: May burst if heated.

GHS Precaution Phrases: P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.
P211: Do not spray on open flame or any other ignition source.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P251: Pressurized container: Do not pierce or burn even after use.
P260: Do not breathe dust/fume/gas/mist/vapours/spray.
P264: Wash hands thoroughly after handling.
P362+364: Take off contaminated clothing and wash it before reuse.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves/clothing and eye/face protection.

GHS Response Phrases: P370+378: In case of fire, use foam, alcohol foam, carbon dioxide, dry chemical or water fog for extinction.
P370+378: In case of fire, use foam, alcohol foam, carbon dioxide, dry chemical or water fog for extinction.
P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.



SAFETY DATA SHEET

Silicone Spray

Revision: 08/23/2017
Supersedes Revision: 12/21/2015

P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P363: Wash contaminated clothing before reuse.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

GHS Storage and Disposal Phrases:

P403+233: Store container tightly closed in well-ventilated place.
P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.
P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

Medical Conditions Generally Aggravated By Exposure: None known when used as directed.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
64742-47-8	Hydrotreated light distillate (petroleum)	32.0 %
142-82-5	Heptane	30.0 %
74-98-6	Propane	30.0 %

4. First Aid Measures

Emergency and First Aid Procedures: If swallowed, induce vomiting only on the advice of a physician. If inhaled, remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. In case of skin contact, wipe off with towel. Wash area with soap and water. If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call physician immediately if adverse reaction occurs.

5. Fire Fighting Measures

Flash Pt: NE -156.00 F (-104.4 C) Method Used: Estimate

Explosive Limits: LEL: .7 UEL: 9.5

Autoignition Pt: No data.

Suitable Extinguishing Media: Foam, CO2, dry chemical, water fog.

Fire Fighting Instructions: Wear goggles and self-contained breathing apparatus. Water spray may be ineffective. Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat. If water is used, fog nozzles preferred.

Flammable Properties and Hazards: Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Vapor accumulation can flash or explode if ignited. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention.

Hazardous Combustion Products: No data available.



6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Avoid breathing vapors. Ventilate area. Remove all sources of ignition. Clean up area with absorbent material and place in closed containers for disposal.

7. Handling and Storage

Precautions To Be Taken in Handling: Keep away from heat/sparks/open flames/hot surfaces - No smoking. Do not spray on open flame or any other ignition source. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Pressurized container: Do not pierce or burn even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/clothing and eye/face protection. Keep out of the reach of children.

Precautions To Be Taken in Storing: Store container tightly closed in well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
64742-47-8	Hydrotreated light distillate (petroleum)	PEL: 1000 ppm	TLV: 200 mg/m3	No data.
142-82-5	Heptane	PEL: 500 ppm	TLV: 400 ppm	No data.
74-98-6	Propane	PEL: 1000 ppm	TLV: (2500 ppm)	No data.

Respiratory Equipment (Specify Type): Avoid breathing vapors. Use with adequate ventilation equal to out of doors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use approved air line type respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Eye Protection: Use of safety glasses with splash guards or full face shield is recommended.

Protective Gloves: Solvent resistant gloves required for prolonged or repeated contact.

Other Protective Clothing: Use of solvent resistant aprons or other clothing is recommended.

Engineering Controls (Ventilation etc.): Sufficient to prevent inhalation of solvent vapors. General dilution and/or local exhaust ventilation in volume or pattern to keep PEL/TLV of most hazardous ingredient below acceptable limit and LEL below stated limit.

Work/Hygienic/Maintenance Practices: Eye washes and safety showers in the workplace are recommended.

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Concentrate is clear liquid.

pH: No data.

Melting Point: No data.

Boiling Point: -44.00 F (-42.2 C) - -410.00 F (-245.6 C)

Flash Pt: NE -156.00 F (-104.4 C) Method Used: Estimate

Evaporation Rate: No data.

Flammability (solid, gas): No data available.

Explosive Limits: LEL: .7 UEL: 9.5

Vapor Pressure (vs. Air or mm Hg): No data.

Vapor Density (vs. Air = 1): > air



Specific Gravity (Water = 1): .64
Solubility in Water: No data.
Octanol/Water Partition Coefficient: No data.
Percent Volatile: 60.0 % by weight.
Autoignition Pt: No data.
Decomposition Temperature: No data.
Viscosity: No data.

10. Stability and Reactivity

Stability: Unstable [] Stable [X]
Conditions To Avoid - Instability: Application to hot surfaces. Storage above 120 degrees F. Exposure to open flame.
Incompatibility - Materials To Avoid: Strong oxidizing agents.
Hazardous Decomposition or Byproducts: Fumes may contain carbon monoxide and other toxic fumes.
Possibility of Hazardous Reactions: Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions: No data available.

11. Toxicological Information

Toxicological Information: CAS# 142-82-5:
Other Studies:, TDLo, Oral, Rat, 60.00 GM/KG, 3 W.
Results:
Kidney, Ureter, Bladder: Changes in liver weight.
- National Technical Information Service, Vol/p/yr: OTS0571116,

Other Studies:, TDLo, Oral, Rat, 260.0 GM/KG, 13 W.
Results:
Kidney, Ureter, Bladder: Changes in bladder weight.
Endocrine:Hypoglycemia.
Nutritional and Gross Metabolic:Weight loss or decreased weight gain.
- National Technical Information Service, Vol/p/yr: OTS0571116,

Other Studies:, TCLo, Inhalation, Rat, 4000. PPM, 6 D.
Results:
Brain and Coverings: Recordings from specific areas of CNS.
Sense Organs and Special Senses (Nose, Eye, Ear, and Taste): Ear: Changes in cochlear structure or function.
Nutritional and Gross Metabolic:Weight loss or decreased weight gain.
- Pharmacology and Toxicology, Munksgaard International Pub., POB 2148, Copenhagen K Denmark, Vol/p/yr: 76,41, 1995

Other Studies:, TDLo, Intraperitoneal, Rat, 9625. MG/KG, 7 D.
Results:
Liver: Other changes.
Blood:Changes in serum composition (e.g.
Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels: Multiple enzyme effects.
- Toxicology Letters., Elsevier Science Pub. B.V., POB 211, 1000 AE, Amsterdam 1000



SAFETY DATA SHEET

Silicone Spray

Revision: 08/23/2017
Supersedes Revision: 12/21/2015

AE Netherlands, Vol/p/yr: 14,169, 1982

Other Studies:, TDLo, Intraperitoneal, Rat, 8840. MG/KG, 45 D.

Results:

Liver: Other changes.

Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels:

Phosphatases.

Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels: Hepatic microsomal mixed oxidase (dealkylation, hydroxylation, etc.)

- JAT, Journal of Applied Toxicology., John Wiley & Sons Ltd., Baffins Lane, Chichester, W.Sussex PO19 1UD UK, Vol/p/yr: 8,81, 1988

Acute toxicity, TCLO, Inhalation, Human, 1000. PPM, 6 M.

Results:

Behavioral: Hallucinations, distorted perceptions.

- "U.S. Bureau of Mines Report of Investigation No. 2979," Patty, F.A., and W.P. Yant, 1929 Volume, Vol/p/yr: 2979,-, 1929

Acute toxicity, LC50, Inhalation, Rat, 103.0 GM/M3, 4 H.

Results:

Behavioral: Change in motor activity (specific assay).

Behavioral: Alteration of classical conditioning.

- Gigiena Truda i Professional'nye Zabolevaniya.(Labor Hygiene and Occupational Disease), V/O Mezhdunarodnaya Kniga, Moscow 113095 Russia, Vol/p/yr: 32(10),23, 1988

Acute toxicity, LCLO, Inhalation, Mouse, 59.00 GM/M3, 41 M.

Results:

Behavioral: Convulsions or effect on seizure threshold.

- Biochemische Zeitschrift., For publisher information, see EJBCAI, Berlin Germany, Vol/p/yr: 115,235, 1921

Acute toxicity, LD50, Intravenous, Mouse, 222.0 MG/KG.

Results:

Brain and Coverings: Changes in circulation (hemorrhage,thrombosis, etc.

Lungs, Thorax, or Respiration:Dyspnea.

Gastrointestinal:Nausea or vomiting.

- Journal of Pharmaceutical Sciences., American Pharmaceutical Assoc., 2215 Constitution Ave., NW, Washington, DC 20037, Vol/p/yr: 67,566, 1978

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-47-8	Hydrotreated light distillate (petroleum)	n.a.	n.a.	A4	n.a.
142-82-5	Heptane	n.a.	n.a.	n.a.	n.a.
74-98-6	Propane	n.a.	n.a.	n.a.	n.a.



12. Ecological Information

General Ecological Information:

CAS# 142-82-5:

Effective concentration to 50% of test organisms., Water Flea (*Daphnia magna*), 82500. UG/L, 96 H, Intoxication., Water temperature: 28.00 C (82.4 F) C.

Results:

No observed effect.

- Acute Toxicity of Petroleum Products, Crude Oil and Oil Refinery Effluent on Plankton, Benthic Invertebrates and Fish, Das, P.K.M.K., and S.K. Konar, 1988

LC50, Water Flea (*Daphnia magna*), 50.00 MG/L, 24 H, Intoxication., Water temperature: 20.00 C (68.0 F) - 22.00 C (71.6 F) C, pH: 7.70, Hardness: 16.00 dH.

Results:

No observed effect.

- Results of the Damaging Effect of Water Pollutants on *Daphnia magna* (Befunde der Schadwirkung Wassergefährdender Stoffe Gegen *Daphnia magna*), Bringmann, G., and R. Kuhn, 1977

LC50, Western Mosquitofish (*Gambusia affinis*), adult(s), 4924000. UG/L, 48 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.

Results:

Age Effects.

- Toxicity to *Gambusia affinis* of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

LC50, Western Mosquitofish (*Gambusia affinis*), adult(s), 4924000. UG/L, 24 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.

Results:

Age Effects.

- Toxicity to *Gambusia affinis* of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

Not reported., Western Mosquitofish (*Gambusia affinis*), adult(s), 5600000. UG/L, 96 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.

Results:

No observed effect.

- Toxicity to *Gambusia affinis* of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

LC50, Western Mosquitofish (*Gambusia affinis*), adult(s), 4924000. UG/L, 96 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.

Results:

No observed effect.

- Toxicity to *Gambusia affinis* of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

Not reported., Coho Salmon, Silver Salmon (*Oncorhynchus kisutch*), 100000. UG/L, 96 H, Mortality, Water temperature: 8.00 C (46.4 F) C, pH: 8.10.

Results:

Age Effects.

- Effects of Some Components of Crude Oil on Young Coho Salmon, Morrow, J.E., R.L. Gritz, and M.P. Kirton, 1975



SAFETY DATA SHEET

Silicone Spray

Revision: 08/23/2017

Supersedes Revision: 12/21/2015

LC50, Mozambique Tilapia (*Oreochromis mossambicus*), 375000. UG/L, 96 H, Mortality, Water temperature: 27.80 C (82.0 F) C.

Results:

No observed effect.

- Acute Toxicity of n-Heptane and n-Hexane on Worm and Fish, Ghatak, D.B., M.M. Hossain, and S.K. Konar, 1988

LC50, Midge Family (Chironomidae), larva(e), 838000. UG/L, 96 H, Intoxication,, Water temperature: 28.00 C (82.4 F) C, pH: 7.00, Hardness: 260.00 MG/L.

Results:

No observed effect.

- Acute Toxicity of Petroleum Products, Crude Oil and Oil Refinery Effluent on Plankton, Benthic Invertebrates and Fish, Das, P.K.M.K., and S.K. Konar, 1988

Effective concentration to 50% of test organisms., Algae (Algae), 1500. UG/L, 8 H, Physiology.

Results:

No observed effect.

- Gulf Underwater Flare Experiment (GUFEX): Effects of Hydrocarbons on Phytoplankton, Brooks, J.M., G.A. Fryxell, D.F. Reid, and W.M. Sackett, 1977

Not reported., Pacific Oyster (*Crassostrea gigas*), egg(s), 3400000. UG/L, 48 H, Mortality, Water temperature: 20.00 C (68.0 F) - 21.50 C (70.7 F) C.

Results:

No observed effect.

- The Effect of Alaskan Crude Oil and Selected Hydrocarbon Compounds on Embryonic Development of the Pacific Oyster, *Crassostrea gigas*, Legore, R.S., 1974

LC50, Oligochaete (*Branchiura sowerbyi*), 2500000. UG/L, 96 H, Mortality, Water temperature: 27.80 C (82.0 F) C.

Results:

No observed effect.

- Acute Toxicity of n-Heptane and n-Hexane on Worm and Fish, Ghatak, D.B., M.M. Hossain, and S.K. Konar, 1988

Effective concentration to 50% of test organisms., Snail (*Viviparus bengalensis*), 472000. UG/L, 96 H, Intoxication,, Water temperature: 28.00 C (82.4 F) C.

Results:

No observed effect.

- Acute Toxicity of Petroleum Products, Crude Oil and Oil Refinery Effluent on Plankton, Benthic Invertebrates and Fish, Das, P.K.M.K., and S.K. Konar, 1988

Lethal concentration to 0% of test organisms., Carp (*Leuciscus idus ssp. melanotus*), 220.0 MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

LC50, Carp (*Leuciscus idus ssp. melanotus*), 270.0 MG/L, 48 H, Mortality.

Results:

No observed effect.



SAFETY DATA SHEET

Silicone Spray

Revision: 08/23/2017

Supersedes Revision: 12/21/2015

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

Lethal concentration to 100% of test organisms., Carp (Leuciscus idus ssp. melanotus), 350.0 MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

Lethal concentration to 0% of test organisms., Carp (Leuciscus idus ssp. melanotus), 1370. MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

LC50, Carp (Leuciscus idus ssp. melanotus), 2940. MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

Lethal concentration to 100% of test organisms., Carp (Leuciscus idus ssp. melanotus), 3420. MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

13. Disposal Considerations

Waste Disposal Method: Dispose of contents/container in accordance with local/regional/national/international regulation.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Aerosols, 2.1, Ltd. Qty
DOT Hazard Class: 2.1 FLAMMABLE GAS
UN/NA Number: UN1950

LAND TRANSPORT (European ADR/RID):

ADR/RID Shipping Name: Aerosols, 2.1, Ltd. Qty
UN Number: 1950
Hazard Class: 2.1 - FLAMMABLE GAS **ADR Classification:** 2.1



SAFETY DATA SHEET

Silicone Spray

Revision: 08/23/2017
Supersedes Revision: 12/21/2015

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name:	Aerosols, 2.1, Ltd. Qty	Packing Group:	
UN Number:	1950	IMDG Classification:	2.1
Hazard Class:	2.1 - FLAMMABLE GAS	IMDG MFAG Number:	
IMDG EMS Page:			

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name:	Aerosols, flammable, 2.1, Ltd Qty	IATA Classification:	
UN Number:	1950		
Hazard Class:	2.1 - FLAMMABLE GAS		2.1

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
64742-47-8	Hydrotreated light distillate (petroleum)	No	No	No
142-82-5	Heptane	No	No	No
74-98-6	Propane	No	No	No

CAS # Hazardous Components (Chemical Name)**Other US EPA or State Lists**

64742-47-8	Hydrotreated light distillate (petroleum)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
142-82-5	Heptane	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test, 8A PAIR; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No
74-98-6	Propane	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 1594; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No

CAS # Hazardous Components (Chemical Name)**International Regulatory Lists**

64742-47-8	Hydrotreated light distillate (petroleum)	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
142-82-5	Heptane	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
74-98-6	Propane	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes



16. Other Information

Revision Date: 08/23/2017

Hazard Rating System:

HEALTH		1
FLAMMABILITY		4
REACTIVITY		0
PPE		

HMIS:

Additional Information About This Product: No data available.

Company Policy or Disclaimer:

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting from use of or reliance upon this information.