

Page: 1

Revision: 09/22/2017

Supersedes Revision: 10/02/2014

according to Regulation (EC) No. 1907/2006 as amended by (EC) No. 1272/2008

## Section 1. Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product Code: C36

Product Name: Disc Brake Quiet

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant identified uses: Disc Brake Quiet

1.3 Details of the Supplier of the Safety Data Sheet:

Company Name: CYCLO INDUSTRIES, INC. Phone Number:

902 SOUTH US HIGHWAY 1 (800)843-7813

JUPITER, FL 33477 USA

Web site address: www.cyclo.com
Email address: ehs@cyclo.com

**Information:** First Aid Emergency (Outside U.S.) (312)906-6194

1.4 Emergency telephone number:

Emergency Contact: First Aid Emergency (800)752-7869

CHEMTREC (703) 527-3887 (800)424-9300

## Section 2. Hazards Identification

### 2.1 Classification of the Substance or Mixture:

Flammable Aerosols, Category 1

Skin Corrosion/Irritation, Category 2

**Toxic To Reproduction, Category 2** 

Specific Target Organ Toxicity (single exposure), Category 3

Specific Target Organ Toxicity (repeated exposure), Category 2

**Aspiration Toxicity, Category 1** 

Aquatic Toxicity (Acute), Category 1

Aquatic Toxicity (Chronic), Category 1

### 2.2 Label Elements:









GHS Signal Word: Danger

### **GHS Hazard Phrases:**

H222: Extremely flammable aerosol.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H335: May cause respiratory irritation.

H361: Suspected of damaging fertility or the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

H400: Very toxic to aquatic life.

H229: Pressurized container: May burst if heated.

Page: 2

Revision: 09/22/2017 Supersedes Revision: 10/02/2014

#### **GHS Precaution Phrases:**

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.

P211: Do not spray on an open flame or any other ignition source.

P251: Pressurized container: Do not pierce or burn, even after use.

P260: Do not breathe dust/fume/gas/mist/vapors/spray.

P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

## **GHS Response Phrases:**

P370+378: In case of fire, use foam, alcohol foam, carbon dioxide, dry chemical or water fog for extinction.

P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P363: Wash contaminated clothing before reuse.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

## **GHS Storage and Disposal Phrases:**

P403+233: Store container tightly closed in well-ventilated place.

P405: Store locked up.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

#### 2.3 Adverse Human Health No data available.

### **Effects and Symptoms:**

## Section 3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)/ REACH Registration No.	Concentration	EC No./ EC Index No.	GHS Classification
142-82-5	Heptane	40.0 -50.0 %	205-563-8 601-008-00-2	Flam. Liq. 2: H225 Asp. Toxic. 1: H304 Skin Corr. 2: H315 STOT (SE) 3: H335 H336 Aquatic (A) 1: H400 Aquatic (C) 1: H410
74-98-6	Propane	10.0 -20.0 %	200-827-9 601-003-00-5	Comp. Gas: H280 Flam. Gas 1: H220
108-88-3	Toluene	10.0 -15.0 %	203-625-9 601-021-00-3	Flam. Liq. 2: H225 Asp. Toxic. 1: H304 Skin Corr. 2: H315 STOT (SE) 3: H335 H336 Toxic Repro. 2: H361d STOT (RE) 2: H373
106-97-8	Butane	1.0 -10.0 %	203-448-7 601-004-01-8	Comp. Gas: H280 Flam. Gas 1: H220



Page: 3

Revision: 09/22/2017 Supersedes Revision: 10/02/2014

## **Section 4. First Aid Measures**

4.1 Description of First AidIf swallowed, seek medical attention immediately. Aspiration hazard: do not induce vomiting or give anything by mouth because this material can enter the lungs and cause Measures:

severe lung damage. Do not leave individual unattended. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. IIf in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of skin contact, wash with soap and water. Remove contaminated clothing and shoes, and launder before reuse. Call physician immediately if adverse reaction occurs.

## Section 5. Fire Fighting Measures

Suitable Extinguishing Carbon dioxide, dry chemicals, foam. 5.1

Media:

5.2 Flammable Properties No data available.

and Hazards:

Hazardous Combustion Carbon dioxide, carbon monoxide.

**Products:** 

**Flammability** NFPA Level 2 Aerosol

Classification:

Flash Pt: <= 0.00 F (-17.8 C) Method Used: TAG Closed Cup LEL: No data. UEL: No data. **Explosive Limits:** 

**Autoignition Pt:** No data.

5.3 **Fire Fighting** EXTREMELY FLAMMABLE. Contents under pressure. Cool exposed containers with

water spray to prevent bursting. SCBA should be used whenever chemical fires are Instructions:

present.

## Section 6. Accidental Release Measures

6.1 Protective Precautions, No data available.

> **Protective Equipment** and Emergency

**Procedures:** 

No data available. 6.2 **Environmental** 

**Precautions:** 

6.3 **Methods and Material** 

For Containment and

Cleaning Up:

Wear appropriate protective clothing and equipment to prevent skin and eye contact. Contain any liquid from leaking containers. Remove sources of ignition. Increase area ventilation. Do not puncture or incinerate container. Contents under pressure. Clean up using dry procedures; avoid dusting. Sweep or gather up material and place in proper container for disposal or recovery. Do not allow to enter sanitary drains, sewer or surface and subsurface waters.

# Section 7. Handling and Storage

7.1 **Precautions To Be** Taken in Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces - No smoking. Do not spray on an open flame or any other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Keep out of the reach of

Page: 4

Revision: 09/22/2017 Supersedes Revision: 10/02/2014

children.

7.2 Precautions To Be

Store container tightly closed in well-ventilated place. Store locked up. Protect from

**Taken in Storing:** sunlight. Do not expose to temperatures exceeding 50C/122F.

## **Section 8. Exposure Controls/Personal Protection**

8.1 Ex	posure Parameters:			
CAS#	<b>Chemical Name</b>	Jurisdiction	Recommended Exposure Limits	Notations
142-82-5	Heptane	ACGIH TLV	TLV: 400 ppm	
		Europe	TWA: 2085. mg/m3 (500. ppm)	
		France VL	TWA: 1668 mg/m3 (400 ppm) STEL: 2085 mg/m3 (500 ppm)	
		OSHA PELs	PEL: 500 ppm	
		Britain EH40	TWA: 2085 mg/m3 (500 ppm) STEL: ()	
74-98-6	Propane	ACGIH TLV	TLV: (2500 ppm)	
		OSHA PELs	PEL: 1000 ppm	
108-88-3	108-88-3 Toluene ACGIH TLV		TLV: 50 ppm	
		Europe	TWA: 192 mg/m3 (50 ppm) STEL: 384 mg/m3 (100 ppm)	
		France VL	TWA: 192 mg/m3 (50 ppm) STEL: 384 mg/m3 (100 ppm)	
		OSHA PELs	PEL: 200 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	
		Britain EH40	TWA: 191 mg/m3 (50 ppm) STEL: 384 mg/m3 (100 ppm)	Skin Absorption
106-97-8	Butane	ACGIH TLV	TLV: (800 ppm)	
		France VL	TWA: 1900 mg/m3 (800 ppm)	
		Britain EH40	TWA: 1450 mg/m3 (600 ppm) STEL: 1810 mg/m3 (750 ppm)	

## 8.2 Exposure Controls:

**8.2.1 Engineering Controls** Exhaust ventilation. Showers. Eyewash stations.

(Ventilation etc.):

8.2.2 Personal protection equipment:

**Eye Protection:** Wear safety glasses or goggles to protect against exposure.

**Protective Gloves:** Use chemical resistant gloves for prolonged skin contact.

Other Protective Rubber apron.

Clothing:

Respiratory Equipment Use an approved NIOSH organic vapor respirator below the TLV. If TLV is exceeded or

**(Specify Type):** overexposure is likely, use positive pressure or self-contained breathing apparatus.

No data available.

Page: 5

Revision: 09/22/2017 Supersedes Revision: 10/02/2014

# **Section 9. Physical and Chemical Properties**

9.1	Information on Basic Physical and Chemical Properties						
	Physical States:		[ ] Gas [ X ] Liqu	uid [ ] Solid			
	Appearance and Odor:		Clear, colorless spray/mist. Typical solvent odor.				
	pH:		No data.				
	Melting Point:		NE				
	Boiling Point:		No data.				
	Flash Pt:		<= 0.00 F (-17.8 C)	Method Used:	TAG Closed Cup		
	<b>Evaporation Rate:</b>		NE				
	Flammability (solid, gas	s):	No data available.				
	<b>Explosive Limits:</b>		LEL: No data.		UEL: No data.		
	Vapor Pressure (vs. Air	or	NE				
	mm Hg):						
	Vapor Density (vs. Air =	= 1):	NE				
	Specific Gravity (Water	= 1):	.81				
	Solubility in Water:		Negligible				
	Octanol/Water Partition		No data.				
	Coefficient:						
	Autoignition Pt:		No data.				
	Decomposition Temper	No data.					
	Viscosity:		NE				
9.2	Other Information						
	Percent Volatile:		88.5 % by weight.				
	Section 10. Stability and Reactivity						
10.1	Reactivity:	No da	ta available.				
10.2	Stability:	Unsta	Unstable [ ] Stable [ X ]				
10.3	Conditions To Avoid -	nditions To Avoid - No data available.					
	<b>Hazardous Reactions:</b>						
	Possibility of	Will o	ccur [ ] Will not o	occur [ X ]			
	<b>Hazardous Reactions:</b>						
10.4	4 Conditions To Avoid - Keep away from heat, sparks and flame. Temperature over 120 degrees F.				emperature over 120 degrees F.		
	Instability:						
10.5	Incompatibility -	Strong	gacids. Strong oxidiz	ing agents.			
	Materials To Avoid:						
10.6	Hazardous	Carbo	n monoxide. Carbon	dioxide.			
	Decomposition or						
	Byproducts:						



Page: 6

Revision: 09/22/2017 Supersedes Revision: 10/02/2014

## Section 11. Toxicological Information

11.1 Information on

CAS# 142-82-5:

**Toxicological Effects:** 

Other Studies:, TDLo, Oral, Rat, 60.00 GM/KG, 3 W.

Results:

Kidney, Ureter, Bladder: Changes in liver weight.

- National Technical Information Service, Vol/p/yr: OTS0571116,

Other Studies:, TDLo, Oral, Rat, 260.0 GM/KG, 13 W.

Results:

Kidney, Ureter, Bladder: Changes in bladder weight.

Endocrine: Hypoglycemia.

Nutritional and Gross Metabolic:Weight loss or decreased weight gain.

- National Technical Information Service, Vol/p/yr: OTS0571116,

Other Studies:, TCLo, Inhalation, Rat, 4000. PPM, 6 D.

Results:

Brain and Coverings: Recordings from specific areas of CNS.

Sense Organs and Special Senses (Nose, Eye, Ear, and Taste): Ear: Changes in cochlear structure or function.

Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

- Pharmacology and Toxicology, Munksgaard International Pub., POB 2148, Copenhagen K Denmark, Vol/p/yr: 76,41, 1995

Other Studies:, TDLo, Intraperitoneal, Rat, 9625. MG/KG, 7 D.

Results:

Liver: Other changes.

Blood:Changes in serum composition (e.g.

Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels: Multiple enzyme effects.

- Toxicology Letters., Elsevier Science Pub. B.V., POB 211, 1000 AE, Amsterdam 1000 AE Netherlands, Vol/p/yr: 14,169, 1982

Other Studies:, TDLo, Intraperitoneal, Rat, 8840. MG/KG, 45 D.

Results:

Liver: Other changes.

Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels:

Phosphatases.

Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels: Hepatic microsomal mixed oxidase (dealkylation, hydroxylation, etc.)

- JAT, Journal of Applied Toxicology., John Wiley & Sons Ltd., Baffins Lane, Chichester, W.Sussex PO19 1UD UK, Vol/p/yr: 8,81, 1988

Acute toxicity, TCLo, Inhalation, Human, 1000. PPM, 6 M.

Results:

Behavioral: Hallucinations, distorted perceptions.

- "U.S. Bureau of Mines Report of Investigation No. 2979," Patty, F.A., and W.P. Yant, 1929 Volume, Vol/p/yr: 2979,-, 1929

Acute toxicity, LC50, Inhalation, Rat, 103.0 GM/M3, 4 H.

Results:

Page: 7

Revision: 09/22/2017 Supersedes Revision: 10/02/2014

Behavioral: Change in motor activity (specific assay).

Behavioral: Alteration of classical conditioning.

 Gigiena Truda i Professional'nye Zabolevaniya. (Labor Hygiene and Occupational Disease), V/O Mezhdunarodnaya Kniga, Moscow 113095 Russia, Vol/p/yr: 32(10),23, 1988

Acute toxicity, LCLO, Inhalation, Mouse, 59.00 GM/M3, 41 M.

Results:

Behavioral: Convulsions or effect on seizure threshold.

- Biochemische Zeitschrift., For publisher information, see EJBCAI, Berlin Germany,

Vol/p/yr: 115,235, 1921

Acute toxicity, LD50, Intravenous, Mouse, 222.0 MG/KG.

Results:

Brain and Coverings: Changes in circulation (hemorrhage,thrombosis, etc.

Lungs, Thorax, or Respiration: Dyspnea.

Gastrointestinal:Nausea or vomiting.

- Journal of Pharmaceutical Sciences., American Pharmaceutical Assoc., 2215

Constitution Ave., NW, Washington, DC 20037, Vol/p/yr: 67,566, 1978

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
142-82-5	Heptane	n.a.	n.a.	n.a.	n.a.
74-98-6	Propane	n.a.	n.a.	n.a.	n.a.
108-88-3	Toluene	n.a.	3	A4	n.a.
106-97-8	Butane	n.a.	n.a.	n.a.	n.a.

## **Section 12. Ecological Information**

### 12.1 Toxicity:

CAS# 142-82-5:

Effective concentration to 50% of test organisms., Water Flea (Daphnia magna), 82500. UG/L, 96 H, Intoxication,, Water temperature: 28.00 C (82.4 F) C.

Results:

No observed effect.

- Acute Toxicity of Petroleum Products, Crude Oil andOil Refinery Effluent on Plankton, Benthic Invertebrates and Fish, Das, P.K.M.K., and S.K. Konar, 1988

LC50, Water Flea (Daphnia magna), 50.00 MG/L, 24 H, Intoxication,, Water temperature: 20.00 C (68.0 F) - 22.00 C (71.6 F) C, pH: 7.70, Hardness: 16.00 dH.

Results:

No observed effect.

- Results of the Damaging Effect of Water Pollutants on Daphnia magna (Befunde der Schadwirkung Wassergefahrdender Stoffe Gegen Daphnia magna), Bringmann, G., and R. Kuhn, 1977

LC50, Western Mosquitofish (Gambusia affinis), adult(s), 4924000. UG/L, 48 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.

Results:

Age Effects.

- Toxicity to Gambusia affinis of Certain Pure Chemicals in Turbid Waters, Wallen, I.E.,



Page: 8

Revision: 09/22/2017 Supersedes Revision: 10/02/2014

W.C. Greer, and R. Lasater, 1957

LC50, Western Mosquitofish (Gambusia affinis), adult(s), 4924000. UG/L, 24 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.

Results:

Age Effects.

- Toxicity to Gambusia affinis of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

Not reported., Western Mosquitofish (Gambusia affinis), adult(s), 5600000. UG/L, 96 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90. Results:

No observed effect.

- Toxicity to Gambusia affinis of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

LC50, Western Mosquitofish (Gambusia affinis), adult(s), 4924000. UG/L, 96 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.

Results:

No observed effect.

- Toxicity to Gambusia affinis of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

Not reported., Coho Salmon, Silver Salmon (Oncorhynchus kisutch), 100000. UG/L, 96 H, Mortality, Water temperature: 8.00 C (46.4 F) C, pH: 8.10.

Results:

Age Effects.

- Effects of Some Components of Crude Oil on Young Coho Salmon, Morrow, J.E., R.L. Gritz, and M.P. Kirton, 1975

LC50, Mozambique Tilapia (Oreochromis mossambicus), 375000. UG/L, 96 H, Mortality, Water temperature: 27.80 C (82.0 F) C.

Results:

No observed effect.

- Acute Toxicity of n-Heptane and n-Hexane on Worm and Fish, Ghatak, D.B., M.M. Hossain, and S.K. Konar, 1988

LC50, Midge Family (Chironomidae), larva(e), 838000. UG/L, 96 H, Intoxication,, Water temperature: 28.00 C (82.4 F) C, pH: 7.00, Hardness: 260.00 MG/L.

Results:

No observed effect.

- Acute Toxicity of Petroleum Products, Crude Oil andOil Refinery Effluent on Plankton, Benthic Invertebrates and Fish, Das, P.K.M.K., and S.K. Konar, 1988

Effective concentration to 50% of test organisms., Algae (Algae), 1500. UG/L, 8 H, Physiology.

Results:

No observed effect.

- Gulf Underwater Flare Experiment (GUFEX): Effects of Hydrocarbons on Phytoplankton, Brooks, J.M., G.A. Fryxell, D.F. Reid, and W.M. Sackett, 1977



Page: 9

Revision: 09/22/2017 Supersedes Revision: 10/02/2014

Not reported., Pacific Oyster (Crassostrea gigas), egg(s), 3400000. UG/L, 48 H, Mortality, Water temperature: 20.00 C (68.0 F) - 21.50 C (70.7 F) C.

Results:

No observed effect.

- The Effect of Alaskan Crude Oil and Selected Hydrocarbon Compounds on Embryonic Development of the Pacfic Oyster, Crassostrea gigas, Legore, R.S., 1974

LC50, Oligochaete (Branchiura sowerbyi), 2500000. UG/L, 96 H, Mortality, Water temperature: 27.80 C (82.0 F) C.

Results:

No observed effect.

- Acute Toxicity of n-Heptane and n-Hexane on Worm and Fish, Ghatak, D.B., M.M. Hossain, and S.K. Konar, 1988

Effective concentration to 50% of test organisms., Snail (Viviparus bengalensis), 472000. UG/L, 96 H, Intoxication,, Water temperature: 28.00 C (82.4 F) C.

Results:

No observed effect.

- Acute Toxicity of Petroleum Products, Crude Oil andOil Refinery Effluent on Plankton, Benthic Invertebrates and Fish, Das, P.K.M.K., and S.K. Konar, 1988

Lethal concentration to 0% of test organisms., Carp (Leuciscus idus ssp. melanotus), 220.0 MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizitat mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

LC50, Carp (Leuciscus idus ssp. melanotus), 270.0 MG/L, 48 H, Mortality. Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizitat mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

Lethal concentration to 100% of test organisms., Carp (Leuciscus idus ssp. melanotus), 350.0 MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizitat mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

Lethal concentration to 0% of test organisms., Carp (Leuciscus idus ssp. melanotus), 1370. MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with



Page: 10

Revision: 09/22/2017 Supersedes Revision: 10/02/2014

the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizitat mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

LC50, Carp (Leuciscus idus ssp. melanotus), 2940. MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizitat mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

Lethal concentration to 100% of test organisms., Carp (Leuciscus idus ssp. melanotus), 3420. MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizitat mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

12.2 Persistence and

No data available.

Degradability:

12.3 Bioaccumulative

No data available.

Potential:

**12.4 Mobility in Soil:** No data available.

12.5 Results of PBT and

No data available.

vPvB assessment:

**12.6** Other adverse effects: No data available.

## **Section 13. Disposal Considerations**

13.1 Waste Disposal

Dispose of contents/container in accordance with local/regional/national/international

Method: regulation.

## **Section 14. Transport Information**

14.1 LAND TRANSPORT (European ADR/RID):

**ADR/RID Shipping Name:** Aerosols, 2,1, Ltd.Qty.

UN Number: 1950

Hazard Class: 2.1 - FLAMMABLE GAS ADR Classification: 2.1

14.2 MARINE TRANSPORT (IMDG/IMO):

**IMDG/IMO Shipping Name:** Aerosols, 2,1, Ltd.Qty.

UN Number: 1950 Packing Group:

Hazard Class: 2.1 - FLAMMABLE GAS IMDG Classification: 2.1

**IMDG MFAG Number:** 

**IMDG EMS Page:** 

14.3 AIR TRANSPORT (ICAO/IATA):

**ICAO/IATA Shipping Name:** Aerosols, flammable, 2.1, Ltd. Qty.

UN Number: 1950

Hazard Class: 2.1 - FLAMMABLE GAS IATA Classification: 2.1



Page: 11

Revision: 09/22/2017 Supersedes Revision: 10/02/2014

# **Section 15. Regulatory Information**

Section 13. Regulatory information						
EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists						
CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)		
142-82-5	Heptane	No	No	No		
74-98-6	Propane	No	No	No		
108-88-3	Toluene	No	Yes 1000 LB	Yes		
106-97-8	Butane	No	No	No		
CAS#	Hazardous Components (Chemical Name)	Other US EPA or State Lists				
142-82-5	Heptane	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test, 8A PAIR; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No				
74-98-6	Propane	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 1594; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No				
108-88-3	Toluene	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A CAIR; CA PROP.65: Yes: RDTox(F); CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: CMR, Part 5; NC TAP: Yes; NJ EHS: Yes - 1866; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes				
106-97-8	Butane	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 0273; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No				
CAS#	Hazardous Components (Chemical Name)	International Regu	latory Lists			
142-82-5	Heptane	Canadian DSL: Yes	s; Canadian NDSL:	No; Taiwan TCSCA:		
74-98-6	Propane	Canadian DSL: Yes	s; Canadian NDSL:	No; Taiwan TCSCA:		
108-88-3	Toluene	Canadian DSL: Yes	s; Canadian NDSL:	No; Taiwan TCSCA:		
106-97-8	Butane	Canadian DSL: Yes	s; Canadian NDSL:	No; Taiwan TCSCA:		

# **Section 16. Other Information**

Yes

**Revision Date:** 09/22/2017

**Hazard Rating System:** 



Additional Information About No data available.

**This Product:** 

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this

MIRS MSDS, (c) A V Systems, Inc.



Page: 12

Revision: 09/22/2017 Supersedes Revision: 10/02/2014

information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting from use of or reliance upon this information.