

### 1. Product and Company Identification

**Product Code:** C43  
**Product Name:** Gas Treatment  
**Company Name:** CYCLO INDUSTRIES  
902 SOUTH US HIGHWAY 1  
JUPITER, FL 33477  
**Phone Number:** (800)843-7813

**Web site address:** www.cyclo.com  
**Email address:** ehs@cyclo.com  
**Emergency Contact:** CHEMTREC (800)424-9300  
001 (703)741-5970

**Intended Use:**

### 2. Hazards Identification

**Acute Toxicity: Inhalation, Category 4**  
**Skin Corrosion/Irritation, Category 2**  
**Serious Eye Damage/Eye Irritation, Category 2B**  
**Carcinogenicity, Category 2**  
**Specific Target Organ Toxicity (repeated exposure), Category 2**  
**Aspiration Toxicity, Category 1**  
**Aquatic Toxicity (Chronic), Category 2**  
**Flammable Liquids, Category 4**



**GHS Signal Word:** **Danger**

**GHS Hazard Phrases:** H227 - Combustible liquid.  
H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H332 - Harmful if inhaled.  
H351 - Suspected of causing cancer.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H411 - Toxic to aquatic life with long lasting effects.

**GHS Precaution Phrases:** P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition source.  
No smoking.  
P233 - Keep container tightly closed.  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

**GHS Response Phrases:** P370+378 - In case of fire, use foam, alcohol foam, carbon dioxide, dry chemical or water fog to extinguish.  
P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P304+341 - IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.  
P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated



# SAFETY DATA SHEET

## Gas Treatment

clothing. Rinse skin with water/shower.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P309+311 - Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

### GHS Storage and Disposal Phrases:

P403 - Store in well-ventilated place.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
68476-34-6	Diesel #2	90.0 -95.0 %
111-76-2	Ethanol, 2-Butoxy-	3.0 -5.0 %
91-20-3	Naphthalene	1.0 -2.0 %
104-76-7	1-Hexanol, 2-Ethyl-	0.5 -1.5 %
NA	Polymer/amine	< 1.0 %
NA	hydroxyethylated aminoethylamide	< 1.0 %

## 4. First Aid Measures

### Emergency and First Aid Procedures:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

### Indication of any immediate medical attention and special treatment needed:

Most important symptoms & effects both acute & delayed: Most important known symptoms & effects are described in the Labeling Section (see Section 2).

## 5. Fire Fighting Measures

**Flash Pt:** 46.60 C (115.9 F) Method Used: Pensky-Marten Closed Cup

**Explosive Limits:** LEL: N.E. UEL: N.E.

**Autoignition Pt:** >= 260.00 C (500.0 F)

**Suitable Extinguishing Media:** Dry chemical, CO2, water spray or alcohol-resistant foam.

**Fire Fighting Instructions:** Use NIOSH/MSHA approved positive pressure self-contained breathing apparatus when any material is involved in a fire.

**Flammable Properties and Hazards:** No data available.

**Hazardous Combustion Products:** No data available.



## 6. Accidental Release Measures

**Steps To Be Taken In Case Material Is Released Or Spilled:** Eliminate sources of ignition. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

## 7. Handling and Storage

**Precautions To Be Taken in Handling:** Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flams and other ignition source. No smoking.  
Keep container tightly closed.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash hands thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Avoid release to the environment.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Keep out of the reach of children.

**Precautions To Be Taken in Storing:** Store in cool/well-ventilated place. Store locked up.

## 8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
68476-34-6	Diesel #2	No data.	TLV: 100 mg/m3	No data.
111-76-2	Ethanol, 2-Butoxy-	PEL: 50 ppm	TLV: 20 ppm	No data.
91-20-3	Naphthalene	PEL: 10 ppm	TLV: 10 ppm STEL: 15 ppm	No data.
104-76-7	1-Hexanol, 2-Ethyl-	No data.	No data.	No data.
NA	Polymer/amine	No data.	No data.	No data.
NA	hydroxyethylated aminoethylamide	PEL: 400 ppm	TLV: 200 ppm STEL: 400 ppm	No data.

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
68476-34-6	Diesel #2	Ontario, CA	TWA: 100 mg/m3 (Inhalable aerosol and vapor)	
111-76-2	Ethanol, 2-Butoxy-	Austria	TWA: 96.9 mg/m3 (20 ppm) STEL: 242 mg/m3 (50 ppm)	Skin Absorption
		California, USA PELs	TWA: 97 mg/m3 (20 ppm)	
		Ontario, CA	TWA: 20 ppm	
		Québec, CA	TWA: 97 mg/m3 (20 ppm)	
		Europe	TWA: 98 mg/m3 (20 ppm) STEL: 246 mg/m3 (50 ppm)	Skin Absorption
		Mexico OEL	TWA: 120 mg/m3 (26 ppm) STEL: 360 mg/m3 (75 ppm)	Skin Absorption
		NIOSH	TWA: 5 ppm	
		New Zealand	TWA: 121 mg/m3 (25 ppm)	
91-20-3	Naphthalene	Austria	TWA: 52 mg/m3 (10 ppm) STEL: 79 mg/m3 (15 ppm)	
		California, USA PELs	TWA: 10 ppm STEL: 15 ppm	Skin Absorption
			TWA: 0.5 mg/m3 (0.1 ppm)	
		Ontario, CA	TWA: 10 ppm STEL: 15 ppm	
		China	TWA: 50 mg/m3	



# SAFETY DATA SHEET

## Gas Treatment

Revision: 04/02/2018  
Supersedes Revision: 01/03/2018

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
91-20-3 (continued)	Naphthalene	Québec, CA	STEL: 75 mg/m3 (15 min) TWA: 52 mg/m3 (10 ppm) STEL: 79 mg/m3 (15 ppm)	
		Europe	TWA: 50 mg/m3 (10 ppm)	
		Mexico OEL	TWA: 50 mg/m3 (10 ppm) STEL: 75 mg/m3 (15 ppm)	
		NIOSH	TWA: 50 mg/m3 (10 ppm) STEL: 75 mg/m3 (15 ppm)	
		New Zealand	TWA: 52 mg/m3 (10 ppm) STEL: 79 mg/m3 (15 ppm)	

<b>Respiratory Equipment (Specify Type):</b>	NIOSH/MSHA approved respirator when exposure is expected to exceed applicable limits.
<b>Eye Protection:</b>	Safety goggles or safety glasses with side shields.
<b>Protective Gloves:</b>	Neoprene, nitrile, polyvinyl alcohol (PVA), polyvinyl chloride and polyurethane gloves to prevent skin contact.
<b>Other Protective Clothing:</b>	Clothes to prevent skin contact.
<b>Engineering Controls (Ventilation etc.):</b>	Local exhaust ventilation as necessary to maintain exposures within applicable limits.

## 9. Physical and Chemical Properties

<b>Physical States:</b>	[ ] Gas [ X ] Liquid [ ] Solid
<b>Appearance and Odor:</b>	Clear red liquid with mild petroleum odor.
<b>pH:</b>	NE
<b>Melting Point:</b>	NE
<b>Boiling Point:</b>	> 360.00 F (182.2 C) - 550.00 F (287.8 C)
<b>Flash Pt:</b>	46.60 C (115.9 F) Method Used: Pensky-Marten Closed Cup
<b>Evaporation Rate:</b>	NE
<b>Flammability (solid, gas):</b>	No data available.
<b>Explosive Limits:</b>	LEL: N.E. UEL: N.E.
<b>Vapor Pressure (vs. Air or mm Hg):</b>	1 - 10 MM_HG at 100.0 F (37.8 C)
<b>Vapor Density (vs. Air = 1):</b>	4 - 5
<b>Specific Gravity (Water = 1):</b>	.81 - .85
<b>Density:</b>	6.87 - 7.06 LB/GA
<b>Solubility in Water:</b>	NE
<b>Saturated Vapor Concentration:</b>	NE
<b>Octanol/Water Partition Coefficient:</b>	No data.
<b>Percent Volatile:</b>	10.0 % by weight.
<b>Autoignition Pt:</b>	>= 260.00 C (500.0 F)
<b>Decomposition Temperature:</b>	NE
<b>Viscosity:</b>	water thin



## 10. Stability and Reactivity

**Stability:** Unstable [ ] Stable [ X ]

**Conditions To Avoid - Instability:** Keep away from heat, sparks & flame.

**Incompatibility - Materials To Avoid:** Acids. Oxidizing materials.

**Hazardous Decomposition or Byproducts:** Oxides of carbon.

**Possibility of Hazardous Reactions:** Will occur [ ] Will not occur [ X ]

**Conditions To Avoid - Hazardous Reactions:** No data available.

## 11. Toxicological Information

**Toxicological Information:** No data available.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
68476-34-6	Diesel #2	n.a.	2B	A3	n.a.
111-76-2	Ethanol, 2-Butoxy-	n.a.	3	A3	n.a.
91-20-3	Naphthalene	Possible	2B	A4	n.a.
104-76-7	1-Hexanol, 2-Ethyl-	n.a.	n.a.	n.a.	n.a.
NA	Polymer/amine	n.a.	n.a.	n.a.	n.a.
NA	hydroxyethylated aminoethylamide	n.a.	n.a.	n.a.	n.a.

## 12. Ecological Information

No data available.

## 13. Disposal Considerations

**Waste Disposal Method:** Dispose of contents/container in accordance with local/regional/national/international regulations.

## 14. Transport Information

### LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Flammable Liquid, n.o.s (Diesel #2), (Diesel #2), III Ltd Qty.  
**DOT Hazard Class:** 3 FLAMMABLE LIQUID  
**UN/NA Number:** UN1993 **Packing Group:** III

### LAND TRANSPORT (Canadian TDG):

**TDG Shipping Name:** Flammable Liquid, n.o.s (Diesel #2), , III Ltd Qty.

### LAND TRANSPORT (European ADR/RID):

**ADR/RID Shipping Name:** Flammable Liquid, n.o.s (Diesel #2), , III Ltd Qty.  
**UN Number:** 1993 **Packing Group:** III  
**Hazard Class:** 3 - FLAMMABLE LIQUID

### MARINE TRANSPORT (IMDG/IMO):

**IMDG/IMO Shipping Name:** Flammable Liquid, n.o.s (Diesel #2), , III Ltd Qty.  
**UN Number:** 1993 **Packing Group:** III  
**Hazard Class:** 3 - FLAMMABLE LIQUID  
**IMDG MFAG Number:**  
**IMDG EMS Page:** **Marine Pollutant:** No



# SAFETY DATA SHEET

## Gas Treatment

Revision: 04/02/2018  
Supersedes Revision: 01/03/2018**AIR TRANSPORT (ICAO/IATA):****ICAO/IATA Shipping Name:** Flammable Liquid, n.o.s (Diesel #2), , III Ltd Qty.

### 15. Regulatory Information

**EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists**

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
68476-34-6	Diesel #2	No	No	No
111-76-2	Ethanol, 2-Butoxy-	No	No	Yes-Cat. N230
91-20-3	Naphthalene	No	Yes 100 LB	Yes
104-76-7	1-Hexanol, 2-Ethyl-	No	No	No
NA	Polymer/amine	No	No	No
NA	hydroxyethylated aminoethylamide	No	No	No

**CAS # Hazardous Components (Chemical Name)****Other US EPA or State Lists**

68476-34-6	Diesel #2	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; FIFRA: Yes - Active - 063514; FDA/DEA CSA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
111-76-2	Ethanol, 2-Butoxy-	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; FIFRA: Yes - Active - 011501, Inert: F/NF/Fr; FDA/DEA CSA: No; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Yes - Cat.; NC TAP: Yes - Cat.; NJ EHS: Yes - Cat.; NY Part 597: No; PA HSL: Yes - 1; SC TAP: Yes - Cat.; WI Air: Yes
91-20-3	Naphthalene	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A PAIR; FIFRA: Yes - Active - 055801, Inert: NF/Fr; FDA/DEA CSA: No; CA PROP.65: Yes: Canc.; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 1322; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes
104-76-7	1-Hexanol, 2-Ethyl-	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 8D TERM; FIFRA: Yes - Active - 079098, Inert: F/NF/Fr; FDA/DEA CSA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No
NA	Polymer/amine	CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; FIFRA: No; FDA/DEA CSA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
NA	hydroxyethylated aminoethylamide	CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; FIFRA: No; FDA/DEA CSA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

**CAS # Hazardous Components (Chemical Name)****International Regulatory Lists**


68476-34-6	Diesel #2	Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC: Yes; China IECSC: Yes; Japan ENCS: Yes - 9-1700; Japan ISHL: No; Korea ECL: Yes - KE-17287; Philippines ICCS: Yes; Taiwan TCSCA: Yes; Singapore HSL: No; REACH: Yes - (R), (P)
------------	-----------	---

111-76-2	Ethanol, 2-Butoxy-	Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC: Yes; China IECSC: Yes; Japan ENCS: Yes - 7-97; Japan ISHL: No; Korea ECL: Yes - KE-04134; Philippines ICCS: Yes; Taiwan TCSCA: Yes; Singapore HSL: No; REACH: Yes - (R), (P)
91-20-3	Naphthalene	Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC: Yes; China IECSC: Yes; Japan ENCS: Yes - 9-2603; Japan ISHL: No; Korea ECL: Yes - KE-25545; Philippines ICCS: Yes; Taiwan TCSCA: Yes; Singapore HSL: No; REACH: Yes - (R), (P)
104-76-7	1-Hexanol, 2-Ethyl-	Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes; Australia ICS: Yes; New Zealand IOC: Yes; China IECSC: Yes; Japan ENCS: Yes - 2-217; Japan ISHL: No; Korea ECL: Yes - KE-13766; Philippines ICCS: Yes; Taiwan TCSCA: Yes; Singapore HSL: No; REACH: Yes - (R), (P)
NA	Polymer/amine	Canadian DSL: No; Canadian NDSL: No; Mexico INSQ: No; Australia ICS: No; New Zealand IOC: No; China IECSC: No; Japan ENCS: No; Japan ISHL: No; Korea ECL: No; Philippines ICCS: No; Taiwan TCSCA: No; Singapore HSL: No; REACH: No
NA	hydroxyethylated aminoethylamide	Canadian DSL: No; Canadian NDSL: No; Mexico INSQ: No; Australia ICS: No; New Zealand IOC: No; China IECSC: No; Japan ENCS: No; Japan ISHL: No; Korea ECL: No; Philippines ICCS: No; Taiwan TCSCA: No; Singapore HSL: No; REACH: No

### 16. Other Information

**Revision Date:** 04/02/2018

**Hazard Rating System:**



**Additional Information About** No data available.

**This Product:**

**Company Policy or**

**Disclaimer:**

Niteo Products, LLC provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Niteo Products, LLC makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Niteo Products, LLC will not be responsible for damages resulting from use of or reliance upon this information.