

according to Regulation (EC) No. 1907/2006 as amended by (EC) No. 1272/2008

Section 1. Identification of the Substance/Mixture and of the Company/Undertaking

- 1.1 Product Code:** C44 & C44B
Product Name: Max 44 Total Fuel System Cleaner
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant identified uses: Fuel Treatment
- 1.3 Details of the Supplier of the Safety Data Sheet:**
- | | | | |
|--------------------------|---|----------------------|---------------|
| Company Name: | CYCLO INDUSTRIES, INC.
902 SOUTH US HIGHWAY 1
JUPITER, FL 33477 USA | Phone Number: | (800)843-7813 |
| Web site address: | www.cyclo.com | | |
| Email address: | ehs@cyclo.com | | |
| Information: | First Aid Emergency (Outside U.S.) | | (312)906-6194 |
- 1.4 Emergency telephone number:**
- | | | |
|---------------------------|-------------------------|---------------|
| Emergency Contact: | First Aid Emergency | (800)752-7869 |
| | CHEMTREC (703) 527-3887 | (800)424-9300 |

Section 2. Hazards Identification

- 2.1 Classification of the Substance or Mixture:**
Acute Toxicity: Inhalation, Category 4
Acute Toxicity: Oral, Category 4
Acute Toxicity: Skin, Category 4
Carcinogenicity, Category 2
Aspiration Toxicity, Category 1
Aquatic Toxicity (Acute), Category 3
Aquatic Toxicity (Chronic), Category 3
- 2.2 Label Elements:**

**GHS Signal Word:** Danger**GHS Hazard Phrases:**

H227: Combustible liquid.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H332: Harmful if inhaled.

H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

H412: Harmful to aquatic life with long lasting effects.



SAFETY DATA SHEET

Max 44 Total Fuel System Cleaner

GHS Precaution Phrases:

- P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.
 P233: Keep container tightly closed.
 P240: Ground/bond container and receiving equipment.
 P241: Use explosion-proof electrical/ventilating/lighting equipment.
 P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264: Wash hands thoroughly after handling.
 P270: Do not eat, drink or smoke when using this product.
 P271: Use only outdoors or in a well-ventilated area.
 P273: Avoid release to the environment.
 P280: Wear protective gloves/clothing and eye/face protection.

GHS Response Phrases:

- P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
 P363: Wash contaminated clothing before reuse.
 P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

GHS Storage and Disposal Phrases:

- P403+235: Store in cool/well-ventilated place.
 H405: Store locked up.
 P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

2.3 Adverse Human Health No data available.**Effects and Symptoms:**

Medical Conditions Irritation from skin exposure may aggravate existing open wounds, skin disorders, and
Generally Aggravated dermatitis (rash).

By Exposure:
Section 3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)/ REACH Registration No.	Concentration	EC No./ EC Index No.	GHS Classification
68476-30-2	Fuel oil, no. 2	90.0 -96.0 %	270-671-4 649-225-00-1	Carcinogen 2: H351
NA	Proprietary Ester	< 5.0 %	NA NA	No data available.
64771-72-8	Paraffins (petroleum), normal C5-C20	0.5 -1.1 %	265-233-4 NA	Asp. Toxic. 1: H304 EUH066
1330-20-7	Xylene (mixed isomers)	0.5 -1.1 %	215-535-7 601-022-00-9	Flam. Liq. 3: H226 Acute Tox.(D) 4: H312 Skin Corr. 2: H315 Acute Tox.(I) 4: H332
91-20-3	Naphthalene	0.01 -0.5 %	202-049-5 601-052-00-2	Acute Tox.(O) 4: H302 Carcinogen 2: H351 Aquatic (A) 1: H400 Aquatic (C) 1: H410
64742-47-8	Hydrotreated light distillate (petroleum)	0.03 -0.3 %	265-149-8 649-422-00-2	Asp. Toxic. 1: H304



SAFETY DATA SHEET

Max 44 Total Fuel System Cleaner

100-41-4 Ethylbenzene

< 0.23 %

202-849-4

601-023-00-4

Revision: 08/16/2017
Supersedes Revision: 02/10/2015Flam. Liq. 2: H225
Acute Tox.(I) 4: H332
STOT (RE) 2: H373
Asp. Toxic. 1: H304

Section 4. First Aid Measures

- 4.1 Description of First Aid Measures:** If swallowed, do not induce vomiting. Rinse mouth. If inhaled, remove to fresh air. If breathing has stopped, apply artificial respiration. If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of skin contact, immediately wash in flowing water for 15 minutes. Immediately remove contaminated clothing. Call physician immediately if adverse reaction occurs.
- 4.2 Important Symptoms and Effects, Both Acute and Delayed:**
Eyes: Mild irritation.
Ingestion: nausea, vomiting, diarrhea and restlessness.
Skin: Irritation and dermatitis.
Inhalation: Headache, giddiness, vertigo and anesthetic stupor.

Section 5. Fire Fighting Measures

- 5.1 Suitable Extinguishing Media:** Avoid using straight water streams. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible. Recommended wearing self-contained breathing apparatus. Water may cause splattering. Material will float on water. Keep run-off water out of sewers and water sources.
- Unsuitable Extinguishing Media:** Toxic fumes, gases or vapors may evolve on burning. Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Container may rupture on heating. Material does not have explosive properties.
- 5.2 Flammable Properties and Hazards:**
Flash Point = 146 +/- 1 F. (Pensky-Martens closed cup)
Autoignition temperature = 489 F
Flammable liquids in air - lower %: 0.7
Flammable limits in air - higher %: 5.0
- Hazardous Combustion Products:** THIS PRODUCT IS CONSIDERED TO BE A COMBUSTIBLE LIQUID PER THE OSHA HAZARD COMMUNICATION STANDARD AND SHOULD BE KEPT AWAY FROM HEAT, FLAME AND SOURCES OF IGNITION. FOR ADDITIONAL FIRE RELATED INFORMATION, SEE NFPA 30 OR THE NORTH AMERICAN EMERGENCY RESPONSE GUIDE 128.
- Flash Pt:** 65.00 C (149.0 F) Method Used: Pensky-Marten Closed Cup
- Explosive Limits:** LEL: .7 at 32.0 F (0.0 C) UEL: 10 at 32.0 F (0.0 C)
- Autoignition Pt:** >= 500.00 F (260.0 C)
- 5.3 Fire Fighting Instructions:** Use NIOSH/MSHA approved positive pressure self-contained breathing apparatus when in a confined area.

Section 6. Accidental Release Measures

- 6.1 Protective Precautions, Protective Equipment and Emergency Procedures:** No data available.
- 6.2 Environmental Precautions:** No data available.
- 6.3 Methods and Material For Containment and Cleaning Up:** Keep public away. Isolate and evacuate the area. Shut off source is safe to do so. Eliminate all ignition sources. Personal Protective Equipment must be worn, see Personal Protection Section for PPE recommendations. Ventilate spill area. Prevent entry into



SAFETY DATA SHEET

Max 44 Total Fuel System Cleaner

Revision: 08/16/2017
Supersedes Revision: 02/10/2015

sewers and waterways. If substance has entered waterway. Advise authorities. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material like sand or soil. Check under Transportation and Labeling (DOT / CERCLA) and Other Regulatory Information

Section (SARA) for hazardous substances to determine regulatory reporting requirements for spills.

Section 7. Handling and Storage

- 7.1 Precautions To Be Taken in Handling:** Keep container tightly closed. Keep away from heat/sparks/open flames/hot surfaces - No smoking. Wear protective gloves/clothing and eye/face protection. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Keep out of the reach of children.
- 7.2 Precautions To Be Taken in Storing:** Store locked up. Store in cool/well-ventilated place.

Section 8. Exposure Controls/Personal Protection

8.1 Exposure Parameters:

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
68476-30-2	Fuel oil, no. 2	ACGIH TLV	TLV: 100 mg/m ³ STEL: 150 ppm	
		OSHA PELs	PEL: 100 ppm	
1330-20-7	Xylene (mixed isomers)	ACGIH TLV	TLV: 100 ppm STEL: 150 ppm CEIL: 25 ppm	
		California, USA PELs	TWA: 100 ppm STEL: 150 ppm CEIL: 300 ppm	
		Mexico OEL	TWA: 435 mg/m ³ (100 ppm) STEL: ()	
		NIOSH	TWA: 100 ppm STEL: 150 ppm	
		OSHA PELs	PEL: 100 ppm	
91-20-3	Naphthalene	ACGIH TLV	TLV: 10 ppm STEL: 15 ppm	
		California, USA PELs	TWA: 10 ppm STEL: 15 ppm	
		Mexico OEL	TWA: 50 mg/m ³ (10 ppm) STEL: 75 mg/m ³ (15 ppm)	
		NIOSH	TWA: 50 mg/m ³ (10 ppm) STEL: 75 mg/m ³ (15 ppm)	
		OSHA PELs	PEL: 10 ppm	
64742-47-8	Hydrotreated light distillate (petroleum)	ACGIH TLV	TLV: 200 mg/m ³	
100-41-4	Ethylbenzene	ACGIH TLV	TLV: 100 ppm STEL: 125 ppm	
		California, USA PELs	TWA: 100 ppm STEL: 125 ppm	
		Mexico OEL	TWA: 435 mg/m ³ (100 ppm) STEL: 545 mg/m ³ (125 ppm)	



SAFETY DATA SHEET

Max 44 Total Fuel System Cleaner

Revision: 08/16/2017
Supersedes Revision: 02/10/2015

100-41-4 Ethylbenzene
(continued)

NIOSH

TWA: 435 mg/m³ (100 ppm)STEL: 545 mg/m³ (125 ppm) (15 min)

OSHA PELs

PEL: 100 ppm

8.2 Exposure Controls:

8.2.1 Engineering Controls (Ventilation etc.): Use local exhaust ventilation to control mists or vapors. Additional ventilation or exhaust may be required to maintain air concentrations below recommended exposure limits.

8.2.2 Personal protection equipment:

Eye Protection: Safety glasses or goggles.

Protective Gloves: Butyl rubber. Neoprene.

Other Protective Clothing: Long sleeve shirt is recommended. Wear either a chemical protective suit or apron when potential for contact with material exists. Use neoprene or nitrile rubber boots when necessary to avoid contaminating shoes. Do not wear rings, watches or similar apparel that could entrap the material and cause a burn.

Respiratory Equipment (Specify Type): Use NIOSH / MSHA approved full face respirator with an organic vapor cartridge if the recommended exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and for large spill clean-up sites.

No data available.

Section 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Clear red liquid with mild petroleum odor.

pH: No data.

Melting Point: No data.

Boiling Point: > 360.00 F (182.2 C) - 550.00 F (287.8 C)

Flash Pt: 65.00 C (149.0 F) Method Used: Pensky-Marten Closed Cup

Evaporation Rate: No data.

Flammability (solid, gas): No data available.

Explosive Limits: LEL: .7 at 32.0 F (0.0 C) UEL: 10 at 32.0 F (0.0 C)

Vapor Pressure (vs. Air or mm Hg): 1 - 10 MM_HG at 100.0 F (37.8 C)

Vapor Density (vs. Air = 1): 4 - 5

Specific Gravity (Water = 1): 0.827 - 0.847

Density: 6.88 - 7.08 LB/GA

Solubility in Water: No data.

Octanol/Water Partition Coefficient: No data.

Autoignition Pt: >= 500.00 F (260.0 C)

Decomposition Temperature: No data.

Viscosity: No data.

9.2 Other Information

Percent Volatile: 10.0 % by weight.



Section 10. Stability and Reactivity

- 10.1 Reactivity:** No data available.
- 10.2 Stability:** Unstable [] Stable [X]
- 10.3 Conditions To Avoid - Hazardous Reactions:** No data available.
- Possibility of Hazardous Reactions:** Will occur [] Will not occur [X]
- 10.4 Conditions To Avoid - Instability:** This material is stable at 22 C, 760 mm pressure. Avoid high temperatures, open flames, sparks, welding, smoking and other ignition sources.
- 10.5 Incompatibility - Materials To Avoid:** Acids, oxidizing agents, halogens and halogenated compounds.
- 10.6 Hazardous Decomposition or Byproducts:** Smoke, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion. Under combustion conditions, oxides of the following elements will be formed: nitrogen.

Section 11. Toxicological Information

- 11.1 Information on Toxicological Effects:**
- Oral Toxicity:** The LD50 in rats is between 2000 mg/kg and 5000 mg/kg. Based on data from components or similar materials. Swallowing this material causes severe irritation and may cause burns of the mouth, esophagus and stomach, abdominal pain, nausea, vomiting and diarrhea. Ingestion may cause CNS depression.
- Eye Irritation:** Corrosive to eyes. Based on data from components or similar materials.
- Skin Irritation:** Corrosive to the skin. Based on data from components or similar material. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, and cracking of the skin.
- Dermal Toxicity:** The following estimated LD 50 is based on incomplete data on components. The LD50 in rabbits is > 2000 mg/Kg. Based on data from components or similar materials. Prolonged or widespread contact with this material could result in the absorption of potentially harmful amounts.
- Inhalation Toxicity:** High concentrations may cause headaches, dizziness, nausea, stupor, and other central nervous system effects leading to visual impairment, difficulty breathing and convulsions.
- Respiratory Irritation:** If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract. Based on data from components and similar materials. Exposure to a high concentration of vapor or mist is irritating to the respiratory tract. Breathing of vapor or mist may aggravate asthma and inflammatory or fibrotic pulmonary disease.
- Dermal Sensitization:** No data available to indicate product or components may be respiratory sensitizes.
- CAS# 68476-30-2:
- Other Studies:**, TDLo, Skin, Species: Rabbit, 100.0 ML/KG, 12 D.
- Results:**
- Skin and Appendages:** Skin: After systemic exposure: Dermatitis, irritative.
- Nutritional and Gross Metabolic:**Weight loss or decreased weight gain.
- Related to Chronic Data - death.**



SAFETY DATA SHEET

Max 44 Total Fuel System Cleaner

Page: 7

Revision: 08/16/2017

Supersedes Revision: 02/10/2015

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982," MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983
Volume, Vol/p/yr: 1,1, 1983

Acute toxicity, LD50, Oral, Rat, 12.00 GM/KG.

Results:

Behavioral: Somnolence (general depressed activity).

- Advances in Modern Environmental Toxicology., Senate Press, Inc., P.O. Box 252, Princeton Junction, NJ 08550, Vol/p/yr: 6,1, 1984

Acute toxicity, LD (Lethal dose), Skin, Species: Rabbit, > 5.000 GM/KG.

Results:

Behavioral: Tremor.

Behavioral: Convulsions or effect on seizure threshold.

- Advances in Modern Environmental Toxicology., Senate Press, Inc., P.O. Box 252, Princeton Junction, NJ 08550, Vol/p/yr: 6,1, 1984

Tumorigenic Effects:, TDLo, Skin, Mouse, 243.0 GM/KG, 97 W.

Results:

Tumorigenic: Carcinogenic by RTECS criteria.

Skin and Appendages: Other: Tumors.

- Fundamental and Applied Toxicology., Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 9,297, 1987

Standard Draize Test, Skin, Species: Rabbit, 500.0 MG, 24 H, Moderate.

Results:

Brain and Coverings: Changes in surface EEG.

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982," MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983
Volume, Vol/p/yr: 1,1, 1983

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, 30 S, Mild.

Results:

Behavioral: Somnolence (general depressed activity).

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982," MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983
Volume, Vol/p/yr: 1,1, 1983

Chronic Toxicological Effects:

Chronic Toxicity: Repeated overexposure to petroleum naphtha can cause nervous system damage. A 14-day dermal toxicity study of 2-ethyhexanol in rats showed blood effects, decreased spleen weight and decreased triglycerides. Repeated overexposure to naphthalene may cause destruction of red blood cells with anemia, fever, jaundice and kidney and liver damage. Repeated ingestion of 2-ethyhexanol may cause injury to the liver and kidneys.

Carcinogenicity: A two-year National Toxicology Program (NTP) study found an increased incidence of tumors of the nose in rats exposed to naphthalene by inhalation. In mice similarly exposed, increased incidence of alveolar / bronchiolar adenomas were observed. Naphthalene has been classified by the International Agency for Research on Cancer (IARC) as a possible human carcinogen (Group 2B) on the basis of sufficient evidence of carcinogenicity in experimental animals but inadequate evidence in exposed



SAFETY DATA SHEET

Max 44 Total Fuel System Cleaner

Revision: 08/16/2017
Supersedes Revision: 02/10/2015

humans. This product is formulated with mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test.

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Reproductive Toxicity: No data available to indicate either product or components present at greater than .1% that may cause reproductive toxicity.

Tertaogenicity: No evidence of adverse effects were found in a developmental toxicity study of 2-ethylhexanol in rats. Doses up to 3 ml/kg applied to the skin during the most critical part of the gestation period produced evidence of toxicity to mothers, but no evidence of injury in the developing offspring. In a previous study, birth defects were observed by oral administration, an unlikely route of exposure in the workplace.

Exposure Limits: Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg. per cubic meter, ACGIH STEL of 10 mg per cubic meter.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
68476-30-2	Fuel oil, no. 2	n.a.	2B	A3	n.a.
NA	Proprietary Ester	n.a.	n.a.	n.a.	n.a.
64771-72-8	Paraffins (petroleum), normal C5-C20	n.a.	n.a.	n.a.	n.a.
1330-20-7	Xylene (mixed isomers)	n.a.	3	A4	n.a.
91-20-3	Naphthalene	Possible	2B	A4	n.a.
64742-47-8	Hydrotreated light distillate (petroleum)	n.a.	n.a.	A4	n.a.
100-41-4	Ethylbenzene	n.a.	2B	A3	n.a.

Section 12. Ecological Information

- 12.1 Toxicity:** Product can cause fouling of shoreline and may be harmful to aquatic life in low concentrations. The 96 hour LC50 values for an accommodated fraction (WAF) of fuel oil ranged from 3.2 to 65 mg/l in fish and 2-210 mg/l in invertebrates, EC 50 values for inhibition of algae growth ranged from 1.8 to 2.9 mg/l for No. 2 fuel oil (the major component of this product) and from 10 to 78 mg/l for diesel fuel. This product does not concentrate or accumulate in the food chain. If released to soil and water, this product is expected to biodegrade under both aerobic and anaerobic conditions.
- 12.2 Persistence and Degradability:** No data available.
- 12.3 Bioaccumulative Potential:** No data available.
- 12.4 Mobility in Soil:** No data available.
- 12.5 Results of PBT and vPvB assessment:** No data available.
- 12.6 Other adverse effects:** No data available.



SAFETY DATA SHEET

Max 44 Total Fuel System Cleaner

Section 13. Disposal Considerations

13.1 Waste Disposal Method: Dispose of contents/container in accordance with local/regional/national/international regulation.

Section 14. Transport Information

14.1 LAND TRANSPORT (European ADR/RID):

ADR/RID Shipping Name: Not-Regulated

UN Number:

Hazard Class:

14.2 MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Not-Regulated

UN Number:

Hazard Class:

Packing Group:

IMDG MFAG Number:

Marine Pollutant: No

IMDG EMS Page:

14.3 AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Not-Regulated

Section 15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
68476-30-2	Fuel oil, no. 2	No	No	No
NA	Proprietary Ester	No	No	No
64771-72-8	Paraffins (petroleum), normal C5-C20	No	No	No
1330-20-7	Xylene (mixed isomers)	No	Yes 100 LB	Yes
91-20-3	Naphthalene	No	Yes 100 LB	Yes
64742-47-8	Hydrotreated light distillate (petroleum)	No	No	No
100-41-4	Ethylbenzene	No	Yes 1000 LB	Yes

CAS # Hazardous Components (Chemical Name)

Other US EPA or State Lists

68476-30-2	Fuel oil, no. 2	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; FDA/DEA CSA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
NA	Proprietary Ester	CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; FDA/DEA CSA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
64771-72-8	Paraffins (petroleum), normal C5-C20	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; FDA/DEA CSA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
1330-20-7	Xylene (mixed isomers)	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; FDA/DEA CSA: No; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: CMR, Part 5; NC TAP: Yes; NJ EHS: Yes - 2014; NY Part



SAFETY DATA SHEET

Max 44 Total Fuel System Cleaner

Revision: 08/16/2017

Supersedes Revision: 02/10/2015

597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes

91-20-3 Naphthalene

CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A PAIR; FDA/DEA CSA: No; CA PROP.65: Yes: Canc.; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 1322; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes

64742-47-8 Hydrotreated light distillate (petroleum)

CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; FDA/DEA CSA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

100-41-4 Ethylbenzene

CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; FDA/DEA CSA: No; CA PROP.65: Yes: Canc.; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 0851; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes

CAS # Hazardous Components (Chemical Name)

68476-30-2 Fuel oil, no. 2

NA Proprietary Ester

64771-72-8 Paraffins (petroleum), normal C5-C20

1330-20-7 Xylene (mixed isomers)

91-20-3 Naphthalene

64742-47-8 Hydrotreated light distillate (petroleum)

100-41-4 Ethylbenzene

International Regulatory Lists

Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: No; Taiwan TCSCA: Yes; REACH: Yes - (R), (P)

Canadian DSL: No; Canadian NDSL: No; Mexico INSQ: No; Taiwan TCSCA: No; REACH: No

Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes; Taiwan TCSCA: Yes; REACH: Yes - (R), (P)


Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes; Taiwan TCSCA: Yes; REACH: Yes - (R), (P)

Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes; Taiwan TCSCA: Yes; REACH: Yes - (R), (P)

Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes; Taiwan TCSCA: Yes; REACH: Yes - (R), (P)

Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes - 1175; Taiwan TCSCA: 116-01 (4); REACH: Yes - (R), (P)

Section 16. Other Information

Revision Date: 08/16/2017**Hazard Rating System:****Additional Information About** No data available.**This Product:****Company Policy or****Disclaimer:**

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting from use of or reliance upon this information.