

### 1. Product and Company Identification

**Product Code:** C44DX & C44DF  
**Product Name:** Max 44 Diesel Fuel System Cleaner  
**Company Name:** CYCLO INDUSTRIES, INC.  
902 SOUTH US HIGHWAY 1  
JUPITER, FL 33477  
**Phone Number:** (800)843-7813

**Web site address:** www.cyclo.com  
**Email address:** ehs@cyclo.com

**Emergency Contact:** First Aid Emergency (800)752-7869  
CHEMTREC (703) 527-3887 (800)424-9300

**Information:** First Aid Emergency (Outside U.S.) (312)906-6194

**Intended Use:** Diesel fuel treatment

### 2. Hazards Identification

Flammable Liquids, Category 3  
Acute Toxicity: Inhalation, Category 4  
Acute Toxicity: Oral, Category 4  
Acute Toxicity: Skin, Category 4  
Serious Eye Damage/Eye Irritation, Category 2A  
Carcinogenicity, Category 2  
Aspiration Toxicity, Category 1  
Skin Corrosion/Irritation, Category 3  
Specific Target Organ Toxicity (single exposure), Category 1



**GHS Signal Word:** Danger

**GHS Hazard Phrases:** H226: Flammable liquid and vapor. H302: Harmful if swallowed.  
H304: May be fatal if swallowed and enters airways.  
H312: Harmful in contact with skin.  
H316: Causes mild skin irritation.  
H319: Causes serious eye irritation. H332: Harmful if inhaled.  
H335: May cause respiratory irritation.  
H336: May cause drowsiness or dizziness.  
H351: Suspected of causing cancer.  
H411: Toxic to aquatic life with long lasting effects.

**GHS Precaution Phrases:** P201: Obtain special instructions before use.  
P202: Do not handle until all safety precautions have been read and understood.  
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264: Wash hands thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P271: Use only outdoors or in a well-ventilated area.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P281: Use personal protective equipment as required.  
P362+364: Take off contaminated clothing and wash it before reuse.

**GHS Response Phrases:** P370+378: In case of fire, use carbon dioxide, foam, dry chemical or water spray to  
P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated  
clothing. Rinse skin with water/shower.  
P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position



comfortable for breathing.

P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P363: Wash contaminated clothing before reuse.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

**GHS Storage and Disposal**

P405: Store locked up.

**Phrases:**

P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

**Medical Conditions Generally Aggravated By Exposure:** Pre-existing skin, respiratory, or other disorders may be aggravated.

**Aggravated By Exposure:**

### 3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
68334-30-5	Diesel fuel	95.0 -96.0 %
111-76-2	Ethanol, 2-Butoxy-	1.5 -2.5 %
91-20-3	Naphthalene	< 0.5 %
95-63-6	1,2,4-Trimethylbenzene	< 0.5 %
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	< 1.0 %
1330-20-7	Xylene (mixed isomers)	< 0.5 %

### 4. First Aid Measures

**Emergency and First Aid Procedures:**

If swallowed, do not induce vomiting. If inhaled, remove to fresh air. Give artificial respiration if needed. If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of skin contact, remove contaminated clothing. Wash affected areas with soap and water. Call physician immediately if adverse reaction occurs.

### 5. Fire Fighting Measures

**Flash Pt:** 131.00 F (55.0 C) Method Used: Closed Cup

**Explosive Limits:** LEL: N.D. UEL: N.D.

**Autoignition Pt:** No data.

**Suitable Extinguishing Media:** Carbon dioxide, foam, dry chemical or water spray.

**Fire Fighting Instructions:** Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Avoid spraying water directly into storage containers due to danger of boil over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode. Combustible fluids can form combustible mixtures at temperatures at or above the flashpoint. Toxic gases will form upon combustion. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Use self-contained breathing apparatus. Do not use solid stream of water, since stream will scatter and spread fire.

**Flammable Properties and Hazards:** No data available.

**Hazardous Combustion Products:** Carbon monoxide and dioxide, partially burnt hydrocarbon gas.



## 6. Accidental Release Measures

**Steps To Be Taken In Case Material Is Released Or Spilled:** Eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without hazard. For small spills, implement cleanup procedure; for large spills implement cleanup procedures, keep public away and advise authorities. Prevent liquid from entering sewers, waterways or low areas. Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust. Recover by pumping (use and explosion proof or hand pump) or with a suitable absorbent. If liquid is too viscous for pumping, scrape up. Remove from water surfaces by skimming or with suitable absorbents.

## 7. Handling and Storage

**Precautions To Be Taken in Handling:** Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash it before reuse. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Keep out of reach of children.

**Precautions To Be Taken in Storing:** Store locked up.

## 8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
68334-30-5	Diesel fuel	No data.	TLV: 100 mg/m3	No data.
111-76-2	Ethanol, 2-Butoxy-	PEL: 50 ppm	TLV: 20 ppm	No data.
91-20-3	Naphthalene	PEL: 10 ppm	TLV: 10 ppm STEL: 15 ppm	No data.
95-63-6	1,2,4-Trimethylbenzene	No data.	No data.	No data.
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	No data.	No data.	No data.
1330-20-7	Xylene (mixed isomers)	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm	No data.

**Respiratory Equipment (Specify Type):** Assure adequate ventilation to keep oil mists under safe limits. When necessary, wear proper NIOSH approved respirators or SCBA.

**Eye Protection:** Safety glasses should be adequate protection under most conditions of use. Wear goggles and/or face shield if splashing or spraying is likely.

**Protective Gloves:** Wear impervious protective gloves, such as Nitrile, Neoprene, or PVA.

**Other Protective Clothing:** Avoid prolonged or repeated skin exposure. Chemicals in mixture can be absorbed through the skin, so prevent contact by wearing impervious protective clothing and long sleeves.

**Engineering Controls (Ventilation etc.):** Required when spraying or using at elevated temperatures that may generate oil mists. Use explosion proof ventilation system.

**Work/Hygienic/Maintenance Practices:** Have suitable eye wash water available. Wash hands with plenty of soap and water before eating, drinking, smoking or using toilet facilities. Take a shower after work if general skin contact occurs. Remove oil soaked clothing and launder before reuse. Launder or discard contaminated leather gloves and shoes.



## 9. Physical and Chemical Properties

<b>Physical States:</b>	[ ] Gas [ X ] Liquid [ ] Solid
<b>Appearance and Odor:</b>	Red liquid with hydrocarbon, aromatic odor.
<b>pH:</b>	NP
<b>Melting Point:</b>	No data.
<b>Boiling Point:</b>	300.00 F (148.9 C)
<b>Flash Pt:</b>	131.00 F (55.0 C) Method Used: Closed Cup
<b>Evaporation Rate:</b>	No data.
<b>Flammability (solid, gas):</b>	No data available.
<b>Explosive Limits:</b>	LEL: N.D. UEL: N.D.
<b>Vapor Pressure (vs. Air or mm Hg):</b>	mmHg 20c:0.5
<b>Vapor Density (vs. Air = 1):</b>	> 2
<b>Specific Gravity (Water = 1):</b>	.91
<b>Solubility in Water:</b>	Negligible
<b>Octanol/Water Partition Coefficient:</b>	No data.
<b>Autoignition Pt:</b>	No data.
<b>Decomposition Temperature:</b>	No data.
<b>Viscosity:</b>	No data.

## 10. Stability and Reactivity

<b>Stability:</b>	Unstable [ ] Stable [ X ]
<b>Conditions To Avoid - Instability:</b>	Excessive heat, sources of ignition, halogens, strong acids, alkalis, oxidizers.
<b>Incompatibility - Materials To Avoid:</b>	Strong oxidizing agents.
<b>Hazardous Decomposition or Byproducts:</b>	Carbon monoxide, hydrocarbons, aldehydes and aromatics, oxides.
<b>Possibility of Hazardous Reactions:</b>	Will occur [ ] Will not occur [ X ]
<b>Conditions To Avoid - Hazardous Reactions:</b>	No data available.



## 11. Toxicological Information

**Toxicological Information:** No data available.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
68334-30-5	Diesel fuel	n.a.	2B	A3	n.a.
111-76-2	Ethanol, 2-Butoxy-	n.a.	3	A3	n.a.
91-20-3	Naphthalene	Possible	2B	A4	n.a.
95-63-6	1,2,4-Trimethylbenzene	n.a.	n.a.	n.a.	n.a.
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	n.a.	n.a.	n.a.	n.a.
1330-20-7	Xylene (mixed isomers)	n.a.	3	A4	n.a.

## 12. Ecological Information

**General Ecological Information:** This product may be toxic to aquatic organisms such as algae and daphnia. This substance has also been shown to be toxic to specific fish species for rainbow trout, Atlantic silverside.

## 13. Disposal Considerations

**Waste Disposal Method:** Dispose of contents/container in accordance with local/regional/national/international regulation.

## 14. Transport Information

### LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Flammable Liquid, n.o.s. (#2 Diesel Fuel, 1,2,4 Trimethylbenzene, Xylene, Solvent Naphtha), Ltd Qty

**DOT Hazard Class:** 3 FLAMMABLE LIQUID

**UN/NA Number:** UN1993 **Packing Group:** III

### LAND TRANSPORT (European ADR/RID):

**ADR/RID Shipping Name:** Flammable Liquid, n.o.s. (#2 Diesel Fuel, 1,2,4 Trimethylbenzene, Xylene, Solvent Naphtha)

**UN Number:** 1993 **Packing Group:** III

**Hazard Class:** 3 - FLAMMABLE LIQUID **ADR Classification:** 3

### MARINE TRANSPORT (IMDG/IMO):

**IMDG/IMO Shipping Name:** Flammable Liquid, n.o.s. (#2 Diesel Fuel, 1,2,4 Trimethylbenzene, Xylene, Solvent Naphtha)

**UN Number:** 1993 **Packing Group:** III

**Hazard Class:** 3 - FLAMMABLE LIQUID **IMDG Classification:** 3

**IMDG EMS Page:** **IMDG MFAG Number:** **Marine Pollutant:** No

### AIR TRANSPORT (ICAO/IATA):

**ICAO/IATA Shipping Name:** Flammable Liquid, n.o.s. (#2 Diesel Fuel, 1,2,4 Trimethylbenzene, Xylene, Solvent Naphtha)

**UN Number:** 1993 **Packing Group:** III

**Hazard Class:** 3 - FLAMMABLE LIQUID **IATA Classification:** 3



## 15. Regulatory Information

**EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists**

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
68334-30-5	Diesel fuel	No	No	No
111-76-2	Ethanol, 2-Butoxy-	No	No	Yes-Cat. N230
91-20-3	Naphthalene	No	Yes 100 LB	Yes
95-63-6	1,2,4-Trimethylbenzene	No	No	Yes
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	No	No	No
1330-20-7	Xylene (mixed isomers)	No	Yes 100 LB	Yes

**CAS # Hazardous Components (Chemical Name)**

**Other US EPA or State Lists**

68334-30-5	Diesel fuel	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
111-76-2	Ethanol, 2-Butoxy-	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Yes - Cat.; NC TAP: Yes - Cat.; NJ EHS: Yes - Cat.; NY Part 597: No; PA HSL: Yes - 1; SC TAP: Yes - Cat.; WI Air: Yes
91-20-3	Naphthalene	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A PAIR; CA PROP.65: Yes: Canc.; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 1322; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes
95-63-6	1,2,4-Trimethylbenzene	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 2716; NY Part 597: No; PA HSL: Yes - E; SC TAP: No; WI Air: No
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
1330-20-7	Xylene (mixed isomers)	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: CMR, Part 5; NC TAP: Yes; NJ EHS: Yes - 2014; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes

**CAS # Hazardous Components (Chemical Name)**


**International Regulatory Lists**

68334-30-5	Diesel fuel	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
111-76-2	Ethanol, 2-Butoxy-	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
91-20-3	Naphthalene	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
95-63-6	1,2,4-Trimethylbenzene	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
1330-20-7	Xylene (mixed isomers)	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

## 16. Other Information

**Revision Date:** 07/20/2017

**Hazard Rating System:**



**Additional Information About** No data available.

**This Product:**

**Company Policy or**

**Disclaimer:**

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting from use of or reliance upon this information.