

according to Regulation (EC) No. 1907/2006 as amended by (EC) No. 1272/2008

Section 1. Identification of the Substance/Mixture and of the Company/Undertaking

- 1.1 Product Code:** C47
Product Name: Octane Boost
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant identified uses: Fuel Treatment
- 1.3 Details of the Supplier of the Safety Data Sheet:**
- | | | |
|--------------------------|---|---------------------------------------|
| Company Name: | CYCLO INDUSTRIES, INC.
902 SOUTH US HIGHWAY 1
JUPITER, FL 33477 USA | Phone Number:
(800)843-7813 |
| Web site address: | www.cyclo.com | |
| Email address: | ehs@cyclo.com | |
| Information: | First Aid Emergency (Outside U.S.) | (312)906-6194 |
- 1.4 Emergency telephone number:**
- | | | |
|---------------------------|-------------------------|---------------|
| Emergency Contact: | First Aid Emergency | (800)752-7869 |
| | CHEMTREC (703) 527-3887 | (800)424-9300 |

Section 2. Hazards Identification

- 2.1 Classification of the Substance or Mixture:**
Acute Toxicity: Inhalation, Category 4
Specific Target Organ Toxicity (single exposure), Category 3
Carcinogenicity, Category 2
Specific Target Organ Toxicity (repeated exposure), Category 2
Aspiration Toxicity, Category 1
Aquatic Toxicity (Chronic), Category 2
Skin Corrosion/Irritation, Category 2

- 2.2 Label Elements:**



GHS Signal Word: Danger

GHS Hazard Phrases:

H227: Combustible liquid.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H332: Harmful if inhaled.
H336: May cause drowsiness or dizziness.
H351: Suspected of causing cancer.
H373: May cause damage to organs through prolonged or repeated exposure.
H411: Toxic to aquatic life with long lasting effects.



GHS Precaution Phrases:

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- P233: Keep container tightly closed.
- P260: Do not breathe dust/fume/gas/mist/vapors/spray.
- P264: Wash hands thoroughly after handling.
- P270: Do not eat, drink or smoke when using this product.
- P273: Avoid release to the environment.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P362+364: Take off contaminated clothing and wash it before reuse.

GHS Response Phrases:

- P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
- P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
- P363: Wash contaminated clothing before reuse.
- P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

GHS Storage and Disposal Phrases:

- P403+235: Store in cool/well-ventilated place.
- P405: Store locked up.
- P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

2.3 Adverse Human Health No data available.

Effects and Symptoms:

Section 3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)/ REACH Registration No.	Concentration	EC No./ EC Index No.	GHS Classification
68476-34-6	Diesel #2	80.0 -90.0 %	270-676-1 649-227-00-2	Carcinogen 2: H351
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	7.5 -8.5 %	265-198-5 649-424-00-3	Asp. Toxic. 1: H304
NA	Polymer Amine Blend	0.5 -1.5 %	NA NA	No data available.
91-20-3	Naphthalene	0.5 -1.0 %	202-049-5 601-052-00-2	Acute Tox.(O) 4: H302 Carcinogen 2: H351 Aquatic (A) 1: H400 Aquatic (C) 1: H410
1330-20-7	Xylene (mixed isomers)	0.4 -0.8 %	215-535-7 601-022-00-9	Flam. Liq. 3: H226 Acute Tox.(D) 4: H312 Skin Corr. 2: H315 Acute Tox.(I) 4: H332
12108-13-3	Manganese, Tricarbonyl methylcyclopentadienyl	0.3 -0.8 %	235-166-5 NA	Flam. Liq. 4: H227 Acute Tox.(O) 2: H300 Acute Tox.(D) 3: H311



SAFETY DATA SHEET

Octane Boost

Revision: 09/06/2017

Supersedes Revision: 02/10/2015

95-63-6	1,2,4-Trimethylbenzene	0.1 -0.2 %	202-436-9 601-043-00-3	Acute Tox.(I) 1: H330 Skin Corr. 3: H316 STOT (SE) 1: H370 STOT (SE) 3: H335 H336 STOT (RE) 2: H373 Aquatic (A) 1: H400 Aquatic (C) 1: H410 Flam. Liq. 3: H226 Skin Corr. 2: H315 Eye Damage 2: H319 Acute Tox.(I) 4: H332 STOT (SE) 3: H335 H336 Aquatic (C) 2: H411
100-41-4	Ethylbenzene	< 0.1 %	202-849-4 601-023-00-4	Flam. Liq. 2: H225 Acute Tox.(I) 4: H332 STOT (RE) 2: H373 Asp. Toxic. 1: H304
108-67-8	Mesitylene	< 0.05 %	203-604-4 601-025-00-5	Flam. Liq. 3: H226 STOT (SE) 3: H335 H336 Aquatic (C) 2: H411
12079-65-1	Manganese, Tricarbonyl(.eta.5-2,4-cyclopentadien-1-yl)-	< 0.01 %	235-142-4 NA	Acute Tox.(O) 2: H300 Acute Tox.(I) 1: H330 Skin Corr. 2: H315 Skin Corr. 3: H316 STOT (SE) 1: H370 STOT (RE) 1: H372

Section 4. First Aid Measures

- 4.1 Description of First Aid Measures:** If swallowed, do not induce vomiting. Rinse mouth. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of skin contact, flush skin with water after contact. Wash contaminated clothing before reuse. Call physician immediately if adverse reaction occurs.
- 4.2 Important Symptoms and Effects, Both Acute and Delayed:**
- Swallowing: Vomiting may result. Pulmonary aspiration hazard if vomiting occurs.
- Breathing: Irritation of the respiratory tract; headache, nausea, dizziness, weakness & fatigue. Extreme exposure can result in unconsciousness & even respiratory arrest.
- Eye Contact: Eye irritant.
- Skin Contact: Prolonged & repeated skin contact may cause defatting & dermatitis.



Section 5. Fire Fighting Measures

- 5.1 Suitable Extinguishing Media:** CO2, dry chemical, foam or other NFPA approved method for treating a Class B fire.
- 5.2 Flammable Properties and Hazards:** Keep containers tightly closed. Isolate from heat and flame. Due to pressure build up, closed containers exposed to extreme heat may explode. Never use a welding or cutting torch ton or near container (even empty) as product or its residue may ignite. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent.
No data available.
- Flash Pt:** 60.60 C (141.1 F) Method Used: Pensky-Marten Closed Cup
- Explosive Limits:** LEL: N.A. UEL: N.A.
- Autoignition Pt:** No data.
- 5.3 Fire Fighting Instructions:** Wear self-contained breathing apparatus and full protective equipment. Water spray may be ineffective. If water is used, fog nozzles are preferable. If exposed to fire or extreme heat, water should be used to cool closed containers and prevent pressure build up or possible autoignition.

Section 6. Accidental Release Measures

- 6.1 Protective Precautions, Protective Equipment and Emergency Procedures:** No data available.
- 6.2 Environmental Precautions:** No data available.
- 6.3 Methods and Material For Containment and Cleaning Up:** Remove all sources of ignition (flames, hot surfaces and electrical, static or frictional sparks). Do not smoke. Prevent breathing of vapors. Ventilate area. Before attempting to clean up, refer to hazard caution information in other sections of this MSDS. Dike and contain spilled material and remove with inert absorbent and non-sparking tools. Store in closed container until product can be properly disposed of. Dispose of in accordance with local, state and federal regulations. Incinerate only in an approved facility. Do not incinerate closed containers.

Section 7. Handling and Storage

- 7.1 Precautions To Be Taken in Handling:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces - No smoking. Keep container tightly closed. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash it before reuse. Keep out of the reach of children.
- 7.2 Precautions To Be Taken in Storing:** Store in cool/well-ventilated place. Store locked up.

Section 8. Exposure Controls/Personal Protection

8.1 Exposure Parameters:

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
68476-34-6	Diesel #2	ACGIH TLV	TLV: 100 mg/m3	
91-20-3	Naphthalene	ACGIH TLV	TLV: 10 ppm	



SAFETY DATA SHEET

Octane Boost

Revision: 09/06/2017
Supersedes Revision: 02/10/2015

91-20-3 Naphthalene (continued)	Europe	STEL: 15 ppm TWA: 50 mg/m3 (10 ppm)	
	France VL	TWA: 50 mg/m3 (10 ppm)	
1330-20-7 Xylene (mixed isomers)	OSHA PELs	PEL: 10 ppm	
	ACGIH TLV	TLV: 100 ppm STEL: 150 ppm	
	Europe	TWA: 221 mg/m3 (50 ppm) STEL: 442 mg/m3 (100 ppm)	Skin Absorption
	France VL	TWA: 221 mg/m3 (50 ppm) STEL: 442 mg/m3 (100 ppm)	
	OSHA PELs	PEL: 100 ppm	
	Britain EH40	TWA: 220 mg/m3 (50 ppm) STEL: 441 mg/m3 (100 ppm)	
12108-13-3 Manganese, Tricarbonyl methylcyclopentadienyl	ACGIH TLV	TLV: 0.2 mg/m3	
	France VL	TWA: 0.2 mg/m3	
95-63-6 1,2,4-Trimethylbenzene	OSHA PELs	CEIL: 5 mg/m3	
	Europe	TWA: 100 mg/m3 (20 ppm)	
	France VL	TWA: 100 mg/m3 (20 ppm) STEL: 250 mg/m3 (50 ppm)	
100-41-4 Ethylbenzene	ACGIH TLV	TLV: 100 ppm STEL: 125 ppm	
	Europe	TWA: 442 mg/m3 (100 ppm) STEL: 884 mg/m3 (200 ppm)	Skin Absorption
	France VL	TWA: 88.4 mg/m3 (20 ppm) STEL: 442 mg/m3 (100 ppm)	
	OSHA PELs	PEL: 100 ppm	
	Britain EH40	TWA: 441 mg/m3 (100 ppm) STEL: 552 mg/m3 (125 ppm)	Skin Absorption
	108-67-8 Mesitylene	Europe	TWA: 100 mg/m3 (20 ppm)
12079-65-1 Manganese, Tricarbonyl(.eta.5-2,4-cyclopentadien-1- yl)-	France VL	TWA: 100 mg/m3 (20 ppm) STEL: 250 mg/m3 (50 ppm)	
	ACGIH TLV	TLV: 0.1 mg/m3	
	France VL	TWA: 0.1 mg/m3	
	OSHA PELs	CEIL: 5 mg/m3	

8.2 Exposure Controls:

8.2.1 Engineering Controls (Ventilation etc.): Use product only with adequate ventilation. Use either local exhaust or mechanical means to meet TLV requirements. Ventilation must be sufficient to limit employee exposure at or below applicable health and safety standards. Heavy solvent vapors should be removed from lower levels of work areas.

8.2.2 Personal protection equipment:

Eye Protection: Chemical goggles.

Protective Gloves: Neoprene or equivalent gloves.

Other Protective Clothing: Solvent impermeable clothing should be worn if contact is likely.

Respiratory Equipment (Specify Type): When used in restricted ventilation areas, wear NIOSH/MDHS approved chemical/mechanical filters designed to remove a combination of particulates & vapor. When used in confined areas, wear NIOSH/MSHA approved air supply respirators or hoods. Follow respirator manufacturer's directions for respirator use. If respirators are



used, a program should be established to assure compliance with OSHS Standard 29 CFR 1910.134.

Work/Hygienic/Mainten Maintain ready access to eye bath & safety shower.
ance Practices:

No data available.

Section 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid
Appearance and Odor: Amber liquid with aromatic odor.
pH: NP
Melting Point: No data.
Boiling Point: >= 250.00 F (121.1 C)
Flash Pt: 60.60 C (141.1 F) Method Used: Pensky-Marten Closed Cup
Evaporation Rate: No data.
Flammability (solid, gas): No data available.
Explosive Limits: LEL: N.A. UEL: N.A.
Vapor Pressure (vs. Air or mm Hg): NA
Vapor Density (vs. Air = 1): NA
Specific Gravity (Water = 1): .901
Solubility in Water: Negligible
Octanol/Water Partition Coefficient: No data.
Autoignition Pt: No data.
Decomposition Temperature: No data.
Viscosity: No data.

9.2 Other Information

Percent Volatile: No data.

Section 10. Stability and Reactivity

10.1 Reactivity: No data available.
10.2 Stability: Unstable [] Stable [X]
10.3 Conditions To Avoid - Hazardous Reactions: No data available.
Possibility of Hazardous Reactions: Will occur [] Will not occur [X]
10.4 Conditions To Avoid - Instability: Heat, sparks, flames.
10.5 Incompatibility - Materials To Avoid: Strong oxidizing agents.
10.6 Hazardous Decomposition or Byproducts: Thermal decomposition may yield carbon monoxide and dioxide.



Section 11. Toxicological Information

11.1 Information on Toxicological Effects:

Animal Data

Naphthalene:

Inhalation 15 minute LC50: >0.34 mg/L in rats
 Skin Absorption LD50: 10,000 mg/kg in rabbits
 Oral LD50: 1,780 mg/kg in rats

Heavy Aromatic Naphtha:

Inhalation 6 hour LC50: >11.67 mg/L in rats
 Skin Absorption LD50: > 3,160 mg/kg in rabbits
 Oral LD50: >5,000 mg/kg in rats

Proprietary Component:

Skin absorption LD50: 660 mg/kg in rabbits
 Oral LD50: 3,990 mg/kg in rats

Heavy Aromatic Naphtha is a severe skin irritant, is an eye irritant, but is not a skin sensitizer in animals. Repeated inhalation exposures caused reduced growth rate, respiratory tract irritation, congestion in liver and spleen, changes in blood tests and equilibrium disturbances. No animal test reports are available to define carcinogenic, mutagenic, developmental, or reproductive hazards.

The Proprietary Component is a severe skin and eye irritant and is a skin sensitizer in animals. Effects of long term dermal exposures include hyperkeratosis and necrosis of the epidermis but no evidence of increased incidences of tumors. Repeated dietary administration of high doses produced depressed liver weights and body weight loss. Tests in animals demonstrate no carcinogenic activity. No animal test reports are available to define developmental or reproductive hazards.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
68476-34-6	Diesel #2	n.a.	2B	A3	n.a.
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	n.a.	n.a.	n.a.	n.a.
NA	Polymer Amine Blend	n.a.	n.a.	n.a.	n.a.
91-20-3	Naphthalene	Possible	2B	A4	n.a.
1330-20-7	Xylene (mixed isomers)	n.a.	3	A4	n.a.
12108-13-3	Manganese, Tricarbonyl methylcyclopentadienyl	n.a.	n.a.	n.a.	n.a.
95-63-6	1,2,4-Trimethylbenzene	n.a.	n.a.	n.a.	n.a.
100-41-4	Ethylbenzene	n.a.	2B	A3	n.a.
108-67-8	Mesitylene	n.a.	n.a.	n.a.	n.a.
12079-65-1	Manganese, Tricarbonyl(.eta.5-2,4-cyclopentadien-1-yl)-	n.a.	n.a.	n.a.	n.a.



Section 12. Ecological Information

- 12.1 Toxicity:** 96 hour LC50, fathead minnows: 4.2-20.8 mg/L
- 12.2 Persistence and Degradability:** No data available.
- 12.3 Bioaccumulative Potential:** No data available.
- 12.4 Mobility in Soil:** No data available.
- 12.5 Results of PBT and vPvB assessment:** No data available.
- 12.6 Other adverse effects:** No data available.

Section 13. Disposal Considerations

- 13.1 Waste Disposal Method:** Dispose of contents/container in accordance with local/regional/national/international regulation.

Section 14. Transport Information

14.1 LAND TRANSPORT (European ADR/RID):

ADR/RID Shipping Name: Not-Regulated

UN Number:

Hazard Class:

14.2 MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Not-Regulated

UN Number:

Hazard Class:

Packing Group:

IMDG MFAG Number:

IMDG EMS Page:

Marine Pollutant:

No

14.3 AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Not-Regulated

Section 15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
68476-34-6	Diesel #2	No	No	No
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	No	No	No
NA	Polymer Amine Blend	No	No	No
91-20-3	Naphthalene	No	Yes 100 LB	Yes
1330-20-7	Xylene (mixed isomers)	No	Yes 100 LB	Yes
12108-13-3	Manganese, Tricarbonyl methylcyclopentadienyl	Yes 100 LB	No	Yes-Cat. N450
95-63-6	1,2,4-Trimethylbenzene	No	No	Yes
100-41-4	Ethylbenzene	No	Yes 1000 LB	Yes
108-67-8	Mesitylene	No	No	No
12079-65-1	Manganese, Tricarbonyl(eta.5-2,4-cyclopentadien-1-yl)-	No	No	Yes-Cat. N450



SAFETY DATA SHEET

Octane Boost


CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
68476-34-6	Diesel #2	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
NA	Polymer Amine Blend	CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
91-20-3	Naphthalene	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A PAIR; CA PROP.65: Yes: Canc.; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 1322; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes
1330-20-7	Xylene (mixed isomers)	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: CMR, Part 5; NC TAP: Yes; NJ EHS: Yes - 2014; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes
12108-13-3	Manganese, Tricarbonyl methylcyclopentadienyl	CAA HAP,ODC: Yes - Cat.; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: Yes - Cat., Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Yes - Cat.; NC TAP: Yes - Cat.; NJ EHS: Yes - 1244; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes - Cat.; WI Air: Yes - Cat.
95-63-6	1,2,4-Trimethylbenzene	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 2716; NY Part 597: No; PA HSL: Yes - E; SC TAP: No; WI Air: No
100-41-4	Ethylbenzene	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: Yes: Canc.; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 0851; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes
108-67-8	Mesitylene	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
12079-65-1	Manganese, Tricarbonyl(eta.5-2,4-cyclopentadien-1-yl)-	CAA HAP,ODC: Yes - Cat.; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: Yes - Cat., Title 8; MA Oil/HazMat: No; MI CMR, Part 5: Yes - Cat.; NC TAP: Yes; NJ EHS: Yes - Cat.; NY Part 597: No; PA HSL: Yes - 1; SC TAP: Yes - Cat.; WI Air: Yes - Cat.
CAS #	Hazardous Components (Chemical Name)	International Regulatory Lists
68476-34-6	Diesel #2	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA:

NA 91-20-3	Polymer Amine Blend Naphthalene	Yes Canadian DSL: No; Canadian NDSL: No; Taiwan TCSCA: No
1330-20-7	Xylene (mixed isomers)	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
12108-13-3	Manganese, Tricarbonyl methylcyclopentadienyl	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
95-63-6	1,2,4-Trimethylbenzene	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
100-41-4	Ethylbenzene	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: 116-01 (4)
108-67-8	Mesitylene	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
12079-65-1	Manganese, Tricarbonyl(.eta.5-2,4-cyclopentadien-1-yl)-	Canadian DSL: No; Canadian NDSL: Yes; Taiwan TCSCA: Yes

Section 16. Other Information

Revision Date: 09/06/2017

Hazard Rating System:



Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting from use of or reliance upon this information.